

Adsorption Study for Chromium (VI) on Iraqi Bentonite

*Khulood A. Al-Sa'adie **

*Sara Badrie Jassim**

Date of acceptance 1/3/2010

Abstract

The subject of this research involves studying adsorption to remove hexavalent chromium Cr(VI) from aqueous solutions.

Adsorption process on bentonite clay as adsorbent was used in the Cr(VI) concentration range (10-100) ppm at different temperatures (298, 303, 308 and 313)K, for different periods of time.

The adsorption isotherms were obtained by obeying Langmuir and Freundlich adsorption isotherm with R^2 (0.9921-0.9060) and (0.994-0.9998), respectively.

The thermodynamic parameters were calculated by using the adsorption process at four different temperatures the values of ΔH , ΔG and ΔS was [(+6.582 – +6.547) kJ.mol⁻¹, (-284.560 – -343.070) kJ.mol⁻¹ and (+0.977 – +1.117) kJ.K⁻¹.mol⁻¹] respectively. This data indicates the spontaneous sorption process.

The kinetic study of adsorption process was studied depending on three kinetic equations:

- 1- Lagergren equation
- 2- Morris-Weber equation
- 3- Reichenberg equation

Keywords:

Introduction

Chromium can exist in several chemical forms, which have oxidation states ranging from 0-VI. However, only trivalent and hexavalent chromium are stable enough to occur in the environment[1,2].

Chromium is a naturally occurring element found in rocks, animals, plants, soil and in volcanic dust and gases[3]. Chromium (VI) in the form of CrO_4^{2-} or $\text{Cr}_2\text{O}_7^{2-}$ and HCrO_4^- , is largely employed in the chemical industry for chrome plating, the manufacture of dyes and pigments, leather tanning, wood preserving, battery, rust and corrosion inhibitors, textiles, electroplating, metal processing, steel fabrication and canning industries[4-9]. Although chromium is used in many industries and is known to be essential trace, but it is found to be toxic and causing cancer at high levels[10].

Toxicological studies are shown that the degree of toxicity of some elements depends on the chemical form in which the element presents, Cr(VI) is more toxicity; by contrast Cr(III) is negligible because it often forms insoluble hydroxides at neutral pH[11,12]. The USA EPA is require (0.05 and 0.1 mg/L) of Cr(VI) in drinking water and inland water, respectively[11,13].

Cr(VI) is known as carcinogens, mutagens, tetragens in biological systems, beside that it can pose health risks such as liver damage, dermatitis, gastro intestinal ulcers, diarrhea, vomiting and nausea[12,14].

The problem of removing pollutants from water are grown with rapid industrialization the discharge of toxic into water courses is a serious pollution problem.

*Department of Chemistry - College of Science - University of Baghdad

Adsorption is the tendency for accumulation of a substance to take place at a surface or at an interface the commencement of adsorption is due to the atoms in any surface being subject to unbalanced forces of attraction perpendicular to the surface plane and these forces possessing a certain unsaturation[15-17].

Langmuir Isotherm is a good representation of chemisorption, and usually represents the low P portion of other isotherms[18].

Langmuir behavior assumes a rapid reversible adsorption, and interaction only between sorbate molecules and a surface site[19,20].

The Langmuir equation could be expressed as:

$$\left[\frac{C_e}{Q} = \frac{1}{k} + \frac{a}{k} \cdot C_e \right] \dots\dots\dots(1)$$

where Q is the amount of adsorbate (mg/g), C_e is the equilibrium concentration (mg/L), and a, k are constants related to adsorption capacity and energy of adsorption respectively or sometimes called Langmuir constants.

Freundlich Isotherm is one of the most important isotherms that deals with sorption at solid-liquid interface. Most of surface are heterogeneous, so the change in potential energy is regular, and the adsorption sites are not equivalent in energy[21,22], hence the multilayer formation is highly expected.

Freundlich equation could be written as follows[23,24]:

$$Q = k_F C_e^{1/n} \dots\dots\dots(2)$$

$$\log Q = \log k_F + 1/n \log C_e \dots\dots\dots(3)$$

where Q is the adsorbate quantity (mg/g), C_e is the concentration of adsorbate at equilibrium (mg/L), k_F , and n is the sorption capacity and an empirical parameter, respectively and also called Freundlich constants.

The major objective of this work is to minimize the concentration of Cr(VI) in aqueous solutions to the acceptable levels, by removing it via and an


adsorption process is used and the optimum conditions for adsorption process have been found. The detailed kinetic and thermodynamics studies have been employed to investigate the mechanism, rate and order of the adsorption process.

Materials and Methods

The bentonite clay was supplied from the state company for geological survey and mining-Iraq, the bentonite had the following composition with particle size less than 75 μ m.


| Constituent | SiO ₂ | Al ₂ O ₃ | CaO | MgO | K ₂ O | Na ₂ O | Fe ₂ O ₃ | L.O.I |
|-------------|------------------|--------------------------------|------|------|------------------|-------------------|--------------------------------|-------|
| Wt% | 56.77 | 15.67 | 4.48 | 3.42 | 0.60 | 1.11 | 5.02 | 12.49 |

The molecular formula of bentonite could be written as:




The spectrophotometer method uses the selective reaction of Cr(VI) with (1,5-DPC) in basic media to yield a red-violet diphenyl carbazone complex.

The general mechanism was illustrated for oxidation of DPC with Cr(VI) was shown in the following equation[2,3].



The suggested final structure of the [Chromium-1,5-diphenylcarbazone] is as follows:



The complex was prepared using 2.5ml (1M) NaOH in volumetric flask 250 ml,

and 50ml of 100ppm Cr(VI) was added to it, 7.5ml of DPC was added (with stirring) to the Cr(VI) solution followed by 2.5ml (50%) H_3PO_4 and then diluted to the mark by distilled water.

A sample of 5 ppm complex solution was taken and a spectrum scan was measured using UV-Vis Spectrophotometer and showed a λ_{max} at 543 nm

The quantity of adsorbate was calculated by using the following formula

$$Q_e = V_{sol} (C_o - C_e) / m \dots\dots\dots(4)$$

Where:

Q_e = Quantity of adsorbate (mg/g).

V_{sol} = Total volume of adsorbate solution (L).

C_o = Initial concentration of adsorbate solutions (mg.L⁻¹).

C_e = Concentration of adsorbate solution at equilibrium (mg.L⁻¹).

m =Weight of adsorbant (g).

While the adsorption percentage was calculated by using the following formula.

$$\%Q = \frac{(C_o - C_e)}{C_o} * 100 \dots\dots\dots(5)$$

Where:

$\%Q$ = Adsorption percentage.

And the adsorption coefficient was calculated by using the following formula[27]:

$$K_{ads} = \frac{Q_e}{C_o} \dots\dots\dots(6)$$

Where:

K_{ads} = The adsorption coefficient.

Results and Discussion

Table (1) and Figure (1) shows the variation of $C_o - C_e$ with the amount of adsorbent (bentonite).

Table -1- The values of ($C_o - C_e$) and M (quantity of sorbent)

| $C_o - C_e$ /mg.L ⁻¹ | M /g |
|---------------------------------|-------|
| 40.18 | 0.050 |
| 40.27 | 0.075 |
| 40.38 | 0.100 |
| 40.30 | 0.150 |
| 40.25 | 0.200 |
| 40.22 | 0.300 |




Fig. -1- The effect of clay dose on the adsorption process for 50 ppm Cr(VI) solution on bentonite at 298K

Table (2) and Figure (2) show the variation of Q_e with the contact time for 50 ppm Cr(VI) solution at 298 K to be in attachment with (0.1g) of bentonite clay.

Table -2- The values of Q_e and C_e at different time for 50 ppm Cr(VI) solution at 298K

| C_e /mg.L ⁻¹ | Q_e /mg.g ⁻¹ | Time /min. |
|---------------------------|---------------------------|------------|
| 9.91 | 4.009 | 5 |
| 9.85 | 4.015 | 10 |
| 9.79 | 4.021 | 15 |
| 9.71 | 4.029 | 20 |
| 9.62 | 4.038 | 30 |
| 9.61 | 4.039 | 40 |
| 9.61 | 4.039 | 50 |
| 9.60 | 4.040 | 60 |




Fig. -2- The variation of Q_e with equilibrium time for 50 ppm Cr(VI) solution at 298K

The pH is an important factor that effected on the adsorption process, Table (3) and Figure (3) show the variation of %Q with different pH values for 50 ppm Cr(VI) solution at 298 K. It's clear that (pH=7) has the maxium Q% value, and this pH was chosen to all experiments of adsorption done subsequently.

Table -3- The adsorption percentage at different pH values, using bentonite at 298K for 50 ppm Cr(VI) solution

| Q% | pH |
|-------|----|
| 79.62 | 3 |
| 79.85 | 5 |
| 80.76 | 7 |
| 79.54 | 9 |
| 79.37 | 11 |




Fig. -3- The adsorption percentage vs. pH, using bentonite at 298K for 50 ppm Cr(VI) solution

The equilibrium adsorption isotherms are of fundamental importance in the design of adsorption systems[(22)]. Table (4) and Figure (4) show the Langmiur data and Linear relationship between C_e/Q_e and C_e of a series Cr(VI) solutions at (298, 303, 308 and 313)K.

Table -4- The values of C_0 , C_e and C_e/Q_e for the adsorption of series Cr(VI) solutions at different temperatures

| 298K | | | 303K | | |
|-------------------------------|-------------------------------|----------------------------------|-------------------------------|-------------------------------|----------------------------------|
| C_0 / mg.L ⁻¹ | C_e / mg.L ⁻¹ | C_e/Q_e / g.L ⁻¹ | C_0 / mg.L ⁻¹ | C_e / mg.L ⁻¹ | C_e/Q_e / g.L ⁻¹ |
| 10 | 2.10 | 2.65 | 10 | 2.22 | 2.85 |
| 20 | 4.08 | 2.55 | 20 | 4.17 | 2.63 |
| 30 | 5.95 | 2.47 | 30 | 6.08 | 2.54 |
| 40 | 7.80 | 2.42 | 40 | 7.93 | 2.47 |
| 50 | 9.62 | 2.38 | 50 | 9.65 | 2.39 |
| 60 | 11.35 | 2.33 | 60 | 11.41 | 2.34 |
| 70 | 12.96 | 2.27 | 70 | 13.05 | 2.29 |
| 80 | 14.58 | 2.22 | 80 | 14.67 | 2.24 |
| 90 | 16.10 | 2.17 | 90 | 16.22 | 2.19 |
| 100 | 17.56 | 2.13 | 100 | 17.61 | 2.13 |

| 308K | | | 313K | | |
|-------------------------------|-------------------------------|----------------------------------|-------------------------------|-------------------------------|----------------------------------|
| C_0 / mg.L ⁻¹ | C_e / mg.L ⁻¹ | C_e/Q_e / g.L ⁻¹ | C_0 / mg.L ⁻¹ | C_e / mg.L ⁻¹ | C_e/Q_e / g.L ⁻¹ |
| 10 | 2.31 | 3.00 | 10 | 2.40 | 3.15 |
| 20 | 4.25 | 2.69 | 20 | 4.36 | 2.78 |
| 30 | 6.17 | 2.59 | 30 | 6.27 | 2.64 |
| 40 | 8.03 | 2.51 | 40 | 8.11 | 2.54 |
| 50 | 9.84 | 2.45 | 50 | 9.92 | 2.49 |
| 60 | 11.55 | 2.38 | 60 | 11.64 | 2.40 |
| 70 | 13.14 | 2.31 | 70 | 13.25 | 2.33 |
| 80 | 14.80 | 2.26 | 80 | 14.86 | 2.28 |
| 90 | 16.37 | 2.22 | 90 | 16.43 | 2.23 |
| 100 | 17.70 | 2.15 | 100 | 17.84 | 2.17 |







Fig. -4- The plot of C_e/Q_e against C_e for the adsorption of series Cr(VI) solutions at different temperatures

Table (5) Show the Langmuir constant at different temperatures

Table -5- The values of Langmuir constant at temperature range (298-313)K

| T (K) | K_L /L/mg | a | R^2 |
|-------|-------------|--------|--------|
| 298 | 0.3721 | 0.0119 | 0.9921 |
| 303 | 0.3528 | 0.0146 | 0.9550 |
| 308 | 0.3392 | 0.0160 | 0.9273 |
| 313 | 0.3256 | 0.0170 | 0.9060 |

Table (6) and Figure (5) show the data and linear relationship of Freundlich isotherm between $\log Q_e$ and $\log C_e$ for the adsorption of Cr(VI) solutions at the temperature range (298-313)K.

Table -6- The values of C_e , $\log C_e$ and $\log Q_e$ for the adsorption of series Cr(VI) solutions at different temperatures

| 298K | | | 303K | | |
|-------------------------------|------------|------------|-------------------------------|------------|------------|
| C_e / mg.L ⁻¹ | $\log C_e$ | $\log Q_e$ | C_e / mg.L ⁻¹ | $\log C_e$ | $\log Q_e$ |
| 10 | 0.322 | -0.102 | 10 | 0.346 | -0.109 |
| 20 | 0.610 | 0.201 | 20 | 0.620 | 0.199 |
| 30 | 0.774 | 0.381 | 30 | 0.783 | 0.378 |
| 40 | 0.892 | 0.507 | 40 | 0.899 | 0.506 |
| 50 | 0.983 | 0.606 | 50 | 0.984 | 0.605 |
| 60 | 1.054 | 0.687 | 60 | 1.057 | 0.686 |
| 70 | 1.112 | 0.756 | 70 | 1.115 | 0.755 |
| 80 | 1.163 | 0.815 | 80 | 1.166 | 0.815 |
| 90 | 1.206 | 0.868 | 90 | 1.210 | 0.867 |
| 100 | 1.244 | 0.916 | 100 | 1.245 | 0.915 |
| 308K | | | 313K | | |
| C_e / mg.L ⁻¹ | $\log C_e$ | $\log Q_e$ | C_e / mg.L ⁻¹ | $\log C_e$ | $\log Q_e$ |
| 10 | 0.363 | -0.114 | 10 | 0.380 | -0.119 |
| 20 | 0.628 | 0.197 | 20 | 0.639 | 0.194 |
| 30 | 0.790 | 0.377 | 30 | 0.797 | 0.375 |
| 40 | 0.904 | 0.504 | 40 | 0.909 | 0.503 |
| 50 | 0.922 | 0.603 | 50 | 0.996 | 0.602 |
| 60 | 1.062 | 0.685 | 60 | 1.065 | 0.684 |
| 70 | 1.118 | 0.754 | 70 | 1.122 | 0.753 |
| 80 | 1.170 | 0.814 | 80 | 1.172 | 0.813 |
| 90 | 1.214 | 0.867 | 90 | 1.215 | 0.866 |
| 100 | 1.247 | 0.915 | 100 | 1.251 | 0.914 |







Fig. -5- Freundlich linear relationship between $\log Q_e$ vs. $\log C_e$ for a series Cr(VI) solutions at different temperature

Table (7) Show the Freundlich constants at different temperatures

Table -7- The values of Freundlich constants at different temperatures

| T (K) | Log k_f | $k_f / \text{mg/g}(\text{mg/L})^n$ | 1/n | n | R ² |
|-------|-----------|------------------------------------|--------|--------|----------------|
| 298 | 0.4679 | 0.3404 | 1.1020 | 0.9074 | 0.9994 |
| 303 | 0.5055 | 0.3122 | 1.1323 | 0.8831 | 0.9997 |
| 308 | 0.5331 | 0.2930 | 1.1523 | 0.8678 | 0.9997 |
| 313 | 0.5638 | 0.2730 | 1.1757 | 0.8505 | 0.9998 |

Table (8) and Figure (6) show that the adsorption percentage of Cr(VI) decrease as temperature increase, where as the adsorption process is an exothermic process, so absorption was involved with adsorption and all processes and all processes increase with temperature increase.

Table -8- The adsorption percentage and Q_e values at different temperature

| T/K | $Q_e / \text{mg.g}^{-1}$ | Q% |
|-----|--------------------------|-------|
| 298 | 4.038 | 80.76 |
| 303 | 4.035 | 80.70 |
| 308 | 4.016 | 80.30 |
| 313 | 4.008 | 80.16 |




Fig. -6- The effect of temperature on the adsorption percentage

The thermodynamic functions, ΔH , ΔG and ΔS were calculated using the following formulas[28,29].

$$b = a \cdot \exp(-\Delta H/RT) \dots\dots\dots(7)$$

$$\ln b = \ln a - (\Delta H/R) \cdot 1/T \dots\dots\dots(8)$$

$$\ln a = \Delta S/R \dots\dots\dots(9)$$

$$\Delta G = \Delta H - T\Delta S \dots\dots\dots(10)$$

Where b is the maximum adsorption quantity for series Cr(VI) solutions at different temperature and could be obtained from the plot of C_e/Q_e vs. C_e (Fig.(4)).

The equation (8) was used to calculate the ΔH , by plotting $\ln b$ vs. $1/T$. Table (9) and Figure (7) showed a linear relationship and the slope represents $-\Delta H/R$, where R is the gas constant ($8.314 \text{ J.mol}^{-1}.\text{K}^{-1}$), and ΔH_{ads} were calculated.

Table -9- The values of the reciprocal of temperature and $\ln b$

| T (K) | $1/T \cdot 10^{-3}$ | b | $\ln b$ |
|-------|---------------------|------|---------|
| 298 | 3.35 | 2.68 | 0.98 |
| 303 | 3.30 | 2.83 | 1.04 |
| 308 | 3.24 | 2.94 | 1.08 |
| 313 | 3.19 | 3.07 | 1.12 |




Fig. -7- The plot of $\ln b$ vs. the reciprocal of temperature

Table -10- Show the thermodynamic functions of the adsorption process

| T (K) | $\Delta H \cdot 10^{-3} (\text{kJ.mol}^{-1})$ | $\Delta G (\text{kJ.mol}^{-1})$ | $\Delta S \cdot 10^{-3} (\text{J.mol}^{-1}.\text{K}^{-1})$ |
|-------|---|---------------------------------|--|
| 298 | 6.55225 | - 284.560 | + 977 |
| 303 | | - 307.680 | + 1037 |
| 308 | | - 325.167 | + 1077 |
| 313 | | - 343.070 | + 1117 |

From the Table (10), It's clear that ΔH has the positive values, which indicate the ideal and the maximum value of a physic-sorption process. All values of ΔG were negative so the adsorption of Cr(VI) on the bentonite was considered a spontaneous process, also ΔS was had the positive values, and it was increased with the temperature increase, the disorder of

the system increase, i.e. the system becomes more disordered, which due to the absorption process and diffusion of Cr(VI) ions in the bentonite pores.

The kinetic of the adsorption process was studied via introducing three models, also the rate constant was calculated.

1- Lagergren Model

The rate constant k_{ads} was determined from the following pseudo-1st-order rate expression, which could be expressed as follows[30]:








$$\ln q_e - q_t = \ln q_e - k_{ads} t \dots \dots \dots (11)$$

where q_t and q_e are the amount of Cr(VI) adsorbed at time t /min., and at equilibrium time respectively, k_{ads} /min.⁻¹ is the rate constant and values are given in Table (11) at 298K.

The linear relationship was obtained via plotting $\ln q_e - q_t$ vs. t /min., as shown in Figure (8).

Table -11- The rate constants of adsorption process for a series Cr(VI) solutions at 298K

| C_o (mg.L ⁻¹) | k_{ad} (min. ⁻¹) | C_o (mg.L ⁻¹) | k_{ad} (min. ⁻¹) |
|-----------------------------|--------------------------------|-----------------------------|--------------------------------|
| 10 | 0.1056 | 60 | 0.0890 |
| 20 | 0.0830 | 70 | 0.0934 |
| 30 | 0.0956 | 80 | 0.1198 |
| 40 | 0.0848 | 90 | 0.0756 |
| 50 | 0.0784 | 100 | 0.1192 |






Fig. -8- The Lagergren model for a series Cr(VI) solutions at 298K

2- Morris-Weber Model

This kinetic model was used to estimate the rate limiting step of any adsorption process, the equation of this model could be expressed as follows^(31,32).

$$q_t = k_d \sqrt{t} \dots\dots\dots (12)$$

Where q_t is the quantity of adsorbed material at any time /mg.g⁻¹, k_d is the diffusion constant, and t is the time of diffusion /min., the plotting of q_t vs. \sqrt{t} was accomplished at 298K. Figure (9) shows the plot of q_t vs. \sqrt{t} for different Cr(VI) concentrations at 298K.




Fig. -9- The plot of q_t vs. \sqrt{t} for a series Cr(VI) solutions at 298K

3- Reichenberg Model

This kinetic model was proposed to discuss the behavior of many adsorption process in solution and Reichenberg had introduced following formula⁽³³⁾:


$$F = [1 - 6/\pi^2] e^{-Bt} \dots\dots\dots(13)$$

$$B_t = -0.4977 - \ln(1-F) \dots\dots\dots(14)$$

$$F = q_t / q_e \dots\dots\dots(15)$$

Plotting of time (min.) vs. B_t revealed a linear relationship with relatively acceptable R^2 values. Figure (10) shows the variation of B_t with time for different concentration of Cr(VI) at 298K.

According to this model, it characterized the rate determining mechanisms which was diffusion process for Cr(VI) ions from the bulk solution to the absorbent surface and absorption occurred.






Fig. -10- The variation of B_t with time for a series of Cr(VI) solutions at 298K

Conclusion

The adsorption of Cr(VI) on bentonite was of Langmuir type at Cr(VI) concentration range (10-1000) ppm. Langmuir type indicates to the monolayer formation of Cr(VI) on the bentonite surface. The isotherms of Cr(VI) was followed both Langmuir and Ferundlich models.

The adsorption of Cr(VI) on bentonite reached to the largest value (83.54) at pH = 7.

References

1. K.N. Upadhyaya, "A text book of Inorganic Chemistry", 2nd ed, (1994).
2. Z. Marczenko, " Spectra Photometric Determination of Elements", (1970).
3. A.S. Mansoor, M.Sc. thesis, Univ. Al- Nahrain, (2008).
4. S.M. Cohen, "Review: Replacement for Chromium Pretreatments on Aluminum", Corrosion, 51(1) (1995), 71-78.
5. S. Kocaoba, G. Akcin, "Removal and Recovery of Chromium and Chromium speciation with MINTEQA2", Talanta, 57(2002), 23-30.

6. R. Petrus. J. Warchol, "Ion exchange between Clinoptilolite and aqueous solution of $\text{Na}^+/\text{Cu}^{2+}$, $\text{Na}^+/\text{Cd}^{2+}$ and $\text{Na}^+/\text{Pd}^{2+}$ ", Micro porous Mesoporous Material, 61(2003), 137-146.
7. F.N. Acar, E. Malkoc, "The removal of Chromium (VI) from Aqueous Solution by Fagus orientalis, Biores. Technol., 94(2004), 13-15.
8. F. Gode, E. Pehlivan, "Sorption of Cr (III) onto chelating b-DAEG-sporopollenin and CEP-Sporopollenin resins", Biores. Technol., 98(2007), 904-911.
9. L.T. Arenas, E. C. Lima, A.A. Sontos, J.C.P. Vaghetti, T.M. Costa, E.V. Benvenuti, "Use of Statical design of experiments to evaluate the sorption capacity of 1,4 – diazoniabicyclo [2.2.2] octane/silica chloride for Cr(VI) adsorption", Colloids and Surfaces, 297(2007) 242-248.
10. G.D. Parkes and Mellor's, "Modern Inorganic Chemistry", (1951).
11. G.F. Nordberg, B.A. Fowler, M.N. Lars, "Hand Book on the toxicology of Metals", Elsevier, (2007).
12. T. A. Kurniawan, G.Y.S. Chon, W.H.Lo, S. Bobel, "Physico Chemical treatment techniques of waste water laden with heavy metals", Chem. Eng. J., 118(2006) 83-88.
13. T. A. Kurniawan, G.Y.S. Chon, W.H.Lo, S. Bobel, "Comparisons of low-cost adsorbents for treating waste water laden with heavy metals" Since of the total Environment, 366(2006) 409-426.
14. A.T. Farideh, S.J. Shahtahari, M.R. Ganjali, J. Hamed, "Design and Performance of Chromium Mist Generator", J. Barz. Chem. Soci. 17(2) (2006), 342-347.
15. J. Gregg, K.S.W. Sing, "Adsorption surface area and Porosity", 2nd ed., Academic Press, London (1982).
16. S.J. Gregg, "The surface chemistry of solids" 2nd ed, London, (1961).
17. R. Defay, I. Rrigoging, A. Bellemans, D.H. Everett, "Surface Tension and adsorption", Longmans, London, (1966).
18. W.G. Frankenburg, E.H. Roldeal, U.I. Komar, Wsky, "Advances in catalysis and related subjects", Academic Press, New York, (1953).
19. A.N.K., "Physical Chemistry", Oxford University Press, 3rd ed, London, (1962).
20. W.J. Moor, "Physical Chemistry" Prentice Hall, 4th ed, Inc., (1972).
21. K.J. Laidre J.H. Misen, "Physical Chemistry", Benjamin Cummings publishing company, California, (1982).
22. W.J. Thomans., B. Crittenden., "Adsorption technology and design", Butter Worth Hiene Mann, (1998).
23. A. Hussien, H. Falah, "Thermodynamic of liquids and solutions", Al-Qadisiyah University, (1993).
24. F. Metcal., and A. Eddy., "Waste water engineering" 3th ed. Wiley, London (1991).
25. Z. Marczenko, "Spectra Photometric Determination of Elements", (1970).
26. A.S. Mansoor, M.Sc. thesis, Univ. Al- Nahrain, (2008).
27. X. Wang, C. Chem, W. Hu, A. Ding, D. Xu, X. Zhou, "Sorption of ^{243}Am (III) to Multiwall Carbon Nanotubes", Envi. Sci: Technol., 39 (2005), 2856-2860.
28. C. Chem. X. Wang, "Adsorption of Ni(II) from aqueous solution using Oxidized Multiwall Carbon Nanotubes", Ind. Eng. Chem. Res., 45(2000) 9144-9149.
29. S. Karaca, A. Gures, M. Acikyildiz, M. Ejder, Adsorption of cationic dye from aqueous solutions by Activated Carbon", Microporous Mesoporous Mater., 115 (2008) 376-382.
30. M.H. Entizari, T.R. Bastami, "Sono-sorption as a new method for the removal of lead ion from aqueous solution", J. Hazard. Mater., B 137 (2006) 959-964.
31. Y.S. Ho. G. McKay, "the kinetic of sorption of divalent metal ions on to

32. sphagnum moss peat", water res., 34 (2000) 735-742.
33. W.S. Won Ngoh, M. Ak. Hanafish, S.S. Yong, "Adsorption of Humic acid from aqueous solution on Cross linked Chitosan-epichlorohydrin beads: Kinetics and isotherm studies", Colloid of surfaces, 65(2008) 18-24.
34. D. Otoniel, S. Lusiene, J. Ricardo, S. Marcelo, "Solid Phase extraction of Cu(II) as diethyl dithiocarbamate (DDTC) complex by polyurethane foam", J. Braz. Chem. Society, 14(5)2003, 728-733.

دراسة امتزاز الكروم السداسي على طين البنتونايت العراقي

سارة بدري جاسم*

خلود عبد صالح السعدي*

*قسم الكيمياء / كلية العلوم / جامعة بغداد

الخلاصة

يتضمن موضوع البحث دراسة امتزاز الكروم السداسي لازالته من المحاليل المائية. عملية الامتزاز على طين البنتونايت (كمادة مازة) لازلة تراكيز مختلفة من الكروم السداسي تراوحت بين (10-1000) ملغم/لتر بمدى من درجات الحرارة (298-313) كلفن وعند الازمان المختلفة. تم الحصول على ايزوثرمات الامتزاز بتطبيق معادلتى لنكماير وفرندلش بنسبة خطية ($R^2=0.9921$) و ($R^2=0.994-0.9998$) على التوالي. تم حساب القيم الثرموديناميكية باربع درجات حرارية وكانت قيم الانثالبي محصورة بين (6.547+ — 6.582) كيلوجول.مول⁻¹ وقيم الطاقة الحرة لكبس بين (284.56- — 343.07) كيلوجول.مول⁻¹ وقيم الانتروبي بين (977+ — 1117) جول.مول⁻¹. بينت القيم تلقائية عملية الامتزاز. تمت دراسة حركيات الامتزاز اعتماداً على ثلاث معادلات حركية هي 1- معادلة لنكماير 2- معادلة موريس-ويبر 3- معادلة ريجمبرغ.