



Available online at www.qu.edu.iq/journalcm

JOURNAL OF AL-QADISIYAH FOR COMPUTER SCIENCE AND MATHEMATICS

ISSN:2521-3504(online) ISSN:2074-0204(print)



Classification and Diseases Identification of Mango Based on Artificial Intelligence: A Review

Israa Mohammed Hassoon

Department of Mathematics, Collage of Science, University of Mustansiriyah (UOM), Baghdad-Iraq. isrmo9@uomustansiriyah.edu.iq.

ARTICLE INFO

Article history:

Received: 15 /09/2022

Revised form: 26/10/2022

Accepted : 30 /10/2022

Available online: 01/12/2022

Keywords:

Mango Classification

Mango Diseases Identification

Shape features

Texture Features

Color features

ABSTRACT

Mango is a drupe fruit which plays an active role in the economy of different countries. Classification process is a fundamental process in: diseases detection domain, sorting and grading. Previously, farmers can detect mango's diseases, identification ripe and unripe mango by their eyes, but it is inaccurate, waste of time and effort. AI technology helping farmers get high quality agricultural crops, the essential idea of AI in agriculture is its flexibility, reliability, speedy performance and applicability. AI technology improves enterprise performance and productivity by automating processes or tasks that once required human skill. AI can also understand data on a scale that no human can achieve, this ability can bring great advantages in the field of agriculture. In this paper, a review for application of artificial intelligence in mango classification and mango diseases identification have been presented.

MSC..

<https://doi.org/10.29304/jqcm.2022.14.4.1085>

1. Introduction.

Mango is one of the best fruits, it is a tasteful, sweet smell, seasonal fruit, there are many kinds of mango fruit which differ in shape, size, sweetness and color of skin. Mango trees are leaving and have different size (small/large), the leaves of mango are classified into: simple, incomplete and petiolate [1]. Artificial intelligence is a branch that intends to create intelligent machines, it is causing a great development and a quantum leap in agriculture by using techniques that are workable, it also helps farmers to get better and higher harvest. Artificial intelligence can provide practical, logical and effective solution for complex problems. It offers image processing, deep learning, machine learning, neural networks and expert system to classify plants [2]. Detecting plant diseases at early stages and classifying the disease are very important. Diseases identification system is essentially in diseases detection. Fungal, viral infection and bacterial diseases which can damage the crop yield by infecting the fruits, leaves and flowers, it caused several types of die back, rot, blotch, anthracnose, scab, spots, etc. so that, early detection of fruit diseases prevent massive crop loss [3,4]. The low yield of mango is due to two reasons: the disease that affecting this fruit and inexperienced farmers cannot detect mango diseases in time. Fruit sorting is significantly depending on fruits appearance, whereas grading is significantly depending on fruits quality. The process of mango sorting is fundamental in "marketing", "export" and "postharvest handling". Today, fruits classification, is important processes for grading and sorting mango in marketing [5]. In this work various techniques are discussed which can help new researchers in the field classification mango and identification mango

*Israa Mohammed Hassoon

Email addresses: isrmo9@uomustansiriyah.edu.iq.

Communicated by 'sub editor'

diseases. This review is organized as the following: Section 2 describes mango classification system; preprocessing methods, features extraction techniques, classification algorithms. Section 3 presents weaknesses and challenges of mango classification system. Section 4 concludes this review.

NOMENCLATURE

Aradius of

Bposition of

Cfurther nomenclature continues down the page inside the text box

2. Classification and Diseases Identification System of Mango

Mango classification/identification system includes three main steps: image preprocessing, feature extraction, and finally classification/identification step.

2.1 preprocessing

Preprocessing is the main process for any system, it performed before the process of feature extraction. It contains different processes such as: converting the input image into a grayscale image, image scaling, contrast adjustment, removing image noise. The input image which was acquired by using high resolution camera, was resized to 256x256 pixels, converted the color space then the region of interest was selected [6]. Images in [7] were acquired by using digital camera, to improve the quality of input image information some preprocessing processes were performed: resizing, image enhancement which was used to select region of interest, the system was worked in 5 seconds to detect mango diseases. A modern and effective preprocessing techniques were used in [8], the system used mango leaves images to identify if the leaf healthier, if not(diseased) the system identified disease's name. Two cameras were used to capture images in [9], mango fruits were collected with different color and size, the images were resized, converted to gray scale and binary then segmentation methods were performed such as: edge-based algorithms, clustering technique, region-based methods and split/merge techniques. Mango leaf images were captured based on digital mobile camera in [10], preprocessing such as: cropping, resizing, noise removing and binarization were performed, to select correct ROI in diseased leaf the "K-means clustering algorithm" was used. Leaf diseases usually carried out by agriculture, in India an automated system was used to classify and identify mango leaf diseases, images were acquired using digital camera, averaging filter was used to remove noise, color transformation (RGB to HSI) and histogram equalization, image segmentation techniques were used [12]. 500 images with resolution of 4320x3240 for each leaf, fruit and flower with healthy/diseased leaf's parts were captured using digital camera in [14], per-processing such as: edge enhancement, gamma correction methodology and segmentation were performed. 3500 leaf images were captured using "digital camera" and "mobile camera", the system was using to detect four diseases of mango leaf [15]. External bacteria disease in Alphonso mango was detected in [17], input images were converted into binary image then processing such as: computing histograms, segmentation were done. In Pakistan an automated system was proposed to identify mango leaves, leaves image were captured by using digital camera, a distance of 2 feet in between mango leaf was kept with white background, all mango leaves images were captured

from peak sight of white surroundings, unwanted noise was removed from image then image was converted to binary image, image enhancement was performed [19]. A novel method was developed in [20] to identify mango leaves, images of mango leaves were captured using digital scanner and stored as a JPJE type with resolution 1700* 2300, colored image was converted to grayscale, median filter was applied then image was converted to binary to perform edge detection process. Mango fruit sorting is based on color of fruit skin and fruit size, color of mango can determine if the fruit was ripe or unripe as in [23], input image was obtained using webcam and sorted as JPEG type then 11 preprocessing steps were performed. In [26] frames were collected from video signal then "deblurring wiener filter" and "pseudo median filter" were performed in order to eliminate motion blur and remove noising, image was converted to binary image, the boundary was traced then maximum axial length was found. Mango in [27] was sorted according to its size and quality, images were captured at Venvi Enterprise with a resolution of 640*480 pixels using digital camera using natural light and white background, after that RGB and Cb of image were calculated, the edge of image was detected, the boundary was traced, the region was identified, the region with the highest boundary length was selected. Machine learning models was developed to predict the ripeness of mangoes at harvest [28], the mango is harvested from the mango field then 120 mango images were utilized, 100 for training data and 20 for testing. A. B. Alejandro et al. [29] proposed an approach to grad and sort mangoes based on their size and physical appearance. Camera with flaps, and conveyor dc motor were connected to the microcontroller to capture images. 100 images were used, some pre-processing operation were performed on input images such as: convert color image to grayscale and binary image, remove noise. In [30] mango images were collected from trees, self-collected trees images were used then bounding box was used to detect mango image. 1200 mango images were used in [31] to classify two kinds of mango using charge-coupled device. In [32] mango was sorted and classified before exporting and packaging to the markets by evaluating mango quality. Images were captured using a CCD with a proper light intensity from a light bulb. 16,777,216 different color images were obtained, images were: resized, converted to grey-scale and binary images, the size of images was calibrated by utilizing images of ellipse. In [33] a system proposed to classify mango by evaluate the maturity of it, 10000 mango images were created using the SEEK thermal camera and smart phone camera. 75% of image were used for training, 25% for testing. In [34] mango grading algorithm was presented, three classes of mangoes are captured: unripe, semi-ripe and ripe, the dataset was contained more than 50 samples for each class, total 400 mango images were obtained using digital camera. Number of pre-processing were performed on images: grayscale image transformation, noise elimination using median filter, segmentation using Otsu thresholding, erosion and dilation. 12 species of mango were classified in [35], 2000 samples from 12 different species of mango were captured, pre-processing steps such that: resizing, labelling of species and scaling were performed. Another approach [36] used for mango grading, mango was classified into: healthy, disease, ripe, unripe, big, medium, very big. 748 samples of mangoes were captured from significant database, the samples were divided into: 169 healthy images, 34 diseased, 192 ripe, 164 unripe, 97 belong to big mango, 41 belong to medium mango and 49 belong to very big mango then pre-processing like: image resizing, noise removing, image segmentation and dilation /erosion were performed. 381 samples were used in [37] to classify mango into rapid and unrapid. In [38] an approach was developed for mango classification and grading of 8 species, mango images with white background were resized to

280 ×260, preprocessing such as: rotation, translation, zooming, shearing, and horizontal flip were performed, 2400 samples were used for classification and 600 samples for grading. Table 1. summarizes the image acquisition, image dataset and image pre-processing steps.

Table 1- Summary of image acquisition, image dataset and image pre-processing steps

Ref.	Image Acquisition Device	Dataset Size	Pre-processing method
S.Raj Kumar and S.Sowrirajan[6]	High Resolution Camera	Not Reported	Grayscale Image Transformation, Scaling, Contrast Adjustment, Removing Image Noise
Veling S. S. et al. [7]	8 Mega Pixel Camera	92	Resizing, Image Enhancement
Priyadharshi ni M. K et al. [8]	Not Reported	100	No Preprocessing Used
Dhameliya S.et al. [9]	Two Cameras	600	Resizing, Gray Scale and Binary Transformation, Edge Detection Clustering, Region-Based Methods and Split/Merge
Sethupathy J. and Veni S. [12]	Digital Camera	25	Remove Noise, Color Transformation (Rgb To Hsi), Histogram Equalization, Segmentation
S. B. Ullagaddi and S.Viswanadha Raju[14]	Nikon 16MP Digital Camera" In [14]	500	Edge Enhancement, Gamma Correction Methodology
Sampada Gulavnai and Rajashri Patil [15]	Sony Digital Camera and Mobile Camera	3500	No Preprocessing Reported
Amritha S Nadarajan and Thamizharasi A. [17]	Digital Camera	100	Binary Image Transformation, Histograms, Segmentation
Maqbool I. et al. [19]	8 Mega Pixel Digital Camera	Not Reported	Binary Image, Image Enhancement

Lakshmi Dutta and Tapan Kumar Basu.[20]	Digital Scanner	80	Converted to Grayscale and Binary Image, Edge Detection
Yossy E.H. et al. [23]	Webcam	52	Rgb And Hsv Transformation, Color Segmentation, Image Morphology Processes, Scaling Thresholding, Find Contours of Image.
Nandi C.S. et al. [26]	Video	16 400	Eliminate Motion Blur and Remove Noising, Binary Transformation, Boundary Tracing Then Maximum Axial Length Was Found
Tomas U. Ganiron Jr. [27]	Camera "Canon Digital IXUS 400	140	Edge Detection, The Boundary Was Traced, The Region Was Identified, The Region with The Highest Boundary Length Was Selected
Denchai W. et al. [28]	Digital Camera	120	Not Reported
A. B. Alejandro et al. [29]	Digital Camera	100	Convert Color Image to Grayscale and Binary Image, Remove Noise
P. Borianne [30]	Digital Camera	10,000	No Pre-Processing Used in Their Study
A. S.A. Mettleq [31]	Charge-Coupled Device	1200	Not Reported
N.T.Thinh [32]	Digital Camera	16,777,216	Resized, Converted to Grey-Scale and Binary Images
V. Bhole[33]	SEEK Thermal Camera and Smart Phone Camera	10000	Not Reported
A. M. Vyas [34]	Camera (Nikon DSLR).	Total 400	Grayscale Image Transformation, Noise Elimination Using Median Filter, Segmentation Using Otsu Thresholding, Erosion and Dilation
S. Girish [35]	Kaggle, Mendeley, Github Image Database	2000	Resizing, Labelling of Species, Scaling, Train-Test Split and Calculate Bottleneck Layer
M. K.Tripathi [36]	From the Internet	748	Image Resizing, Noise Removing, Image Segmentation and Dilation

			/Erosion Were Performed on Mango Images
D. Worasawate. et al. [37]	Parallel plate capacitor sensor	120	SMOTETomek was used for cleaning and balancing the data
H. M. R. Iqbal and A. Hakim [38]	Nikon 7000 camera	2400 for classification, 600 for grading	T ranslation, rotation, zooming, horizontal flip and shearing

2.2 Feature Extraction Process

Feature extraction is fundamental step that includes extraction of characteristics from input image, features extraction process aims to extract significant, correct and unique features that can distinguish an input image from others. Two kinds of features can be extracted from image: first type is shape-based features which describes the whole object, the second type is the geometric-based features which describes the local features of object. Some of approaches used hybrid features as in [6]: texture, color, and geometric features were extracted from input image. Hybrid features used again in [9], shape features and color features were extracted from mango image. Textural features based on GLCM and spatial gray-level dependence matrices were used in [12] to identify and classify the diseases of mango leaves in Indian. Combination of "Wavelet-PCA based statistical features" and "modified rotation kernel transformation based directional features" were used in [14] to extracted features from mango leaf, flower and fruit in order to diagnose of pathological problems in mango. Combination of shape features and RST-Invariant features of mango leaf were extracted in [19] to identify mango. Two features: geometric features (width, area, diameter, mango perimeter) and morphological features (narrow factor, form factor, aspect ratio, rectangularity, smooth factor, ratio of mango perimeter) were extracted to detect ripe and unripe mango [24]. Geometrical features of mango leaves like: length, aspect ratio, width with morphological features were obtained for 80 sample images in [20] to identify the type of a mango tree. Shape and texture features were extracted from mango image in [21] to classify mango in Pakistan. A gain the ripe or unripe mango was detected based on color features which were extracted from mango images [23]. Textural features were used to describe infected part in [7,8], the GLCM method was used to characterize the texture of an image in order to classify mango diseases. Textural features were extracted again in [18], 9 different features were extracted from mango image (1766 images) to develop automated system capable of classifying different types of mango. Eight features (area, solidity, diameter, extent, convex area, number of objects, and major axis length) were extracted from leaf image to classify mango leaf diseases [10]. Color features were extracted in order to identify normal or diseased mango [17]. (13) number of features were extracted based on GLCM from 30 images in [22], the system successfully classified 10 kinds of mango fruits. Sorting of mangoes into number of classes is requisite in mangoes harvesting process, 27 features were extracted in [26] to sorting mango according to its maturity. Mango in [27] was sorting according to its size and quality, features like: area, perimeter, percent defect and roundness were extracted, area and perimeter were used to determine the size of the mango whereas

percent defect and roundness were used to determine the quality of the mango. Features included physical, biochemical and electrical attributes were extracted in [28], 10 attributes such as: green color, weight, red color, TSS, blue color, TSS-TA ratio, weight and capacitance ratio, TA, voltage and capacitance were extracted. In [29] color, black spots and area were extracted, probabilistic neural network was used to classifying mangoes into three classes (small, medium, large). A region of interest pooling was performed in [30] using mango features that extracted by the convolution neural network, Faster R-CNN network was used for identification and detection processes, 7000 images used for validation, 3,000 for testing, the results of validations showed that undertake additional relaxation was necessary for more R-CNN Faster network relevant predictions respected to users' expectations. A gain in [31] an approach used to classify two mango species, the data set that used was contained 1200 samples, 90% of it used for training, 10% for validation, the training accuracy was 100%. In [32][33] a system was designed to evaluate mango quality and maturity based on mango shape features, mango was classified in terms of volume, density, color, shape, size and maturity into three classes according to mango quality: extra Class-I, and Class-II. In [34] color and size features were extracted, mango was classified into four types: unripe, semi-ripe, ripe or rejected based on the extracted features with 10 grading rules. In [35] CNN with transfer learning used to classify mango, 2000 mango samples were used, 80% of samples for training and the rest samples 20% for testing and validation. In [36] shape, texture and color features were extracted then lion assisted firefly algorithm was used to select relevant features, the selected features fed to CNN, at last mango category was identified. Ten features from three types of features: physical features, electrical features and biochemical features were extracted in [37] then fed to machine learning for classification. In [38] texture, color, shape, and size features were extracted then fed to convolutional neural network in order to classify and grade mango. Table 2. summarizes the features and advantages.

Table 2- Summary of the features, advantages

Ref.	Features	Advantages
Velting S. S. et al. [7]	Textural features	Effective mango diseases classification performance
Prakash B. and Yerpude A. [10]	Shape features	compliant feature selection and high accuracy diseases identification
S. B. Ullagaddi and S.Viswanadha Raju[14]	Wavelet-PCA based statistical features" and "modified rotation kernel transformation based directional features	An accurate system capable of classifying mango based on various parts (fruit, leaf, flower) with high accuracy
VaniAshok and D.S.Vinod[18]	Textural features	good results of detection defects in mango

Maqbool I. et al. [19]	Shape features and RST-Invariant features	Achieve good results
Behera S.K. et al. [22]	GLCM	Better accuracy for classifying different kinds of mango fruits
Yossy E.H. et al. [23]	Color features	good capability for color texture analysis
Chhabra M. et al. [24]	Geometric features and morphological	Robust features & achieve good results
Nandi C.S. et al. [26]	GLCM	Reliable and adequate method for sorting mango according to its maturity
P. Borianne [30]	Features extracted by CNN	Achieves good results on both identification and detection based on Trees images
A. S.A. Mettleq [31]	Shape features	Achieve high accuracy
V. Bhole[33]	Features extracted by CNN	workable feature selection and high classification accuracy
A. M. Vyas [34]	Color and size features	privileged capability for shape analysis and size of mango
S. Girish [35]	Features extracted by CNN	Achieve high accuracy
M. K.Tripathi [36]	Shape, texture and color features	Robust features & achieve good results for mango grading
D. Worasawate. et al. [37]	physical features, electrical features and biochemical features	Achieve good results
H. M. R. Iqbal and A. Hakim [38]	texture, color, shape, and size features	achieve good accuracy for mango classification and grading

2.3 Classification Process.

In this section various studies of mango identification and classification are illustrated in Table 3.

Table 3- Summary of various studies of mango fruit.

Researcher name	Aim of research	Classification Algorithm	Organ	Accuracy
Sutrodhor N. et al. [4]	Mango Leaf Ailment Detection	Neural Network and support vector machine	Leaf	87.5%
Aboalarbe M. S. and Adl A. [5]	Classifying mango diseases	Machine learning and deep learning algorithms	Leaf	97%
S.Raj Kumar and S.Sowrirajan[6]	Mango diseases detection	Hybrid features with Lloyd's clustering and BPN classifier	Leaf	Not reported
Veling S. S. et al. [7]	Classifying mango diseases	support vector machine	Fruit and leaf	90%
Priyadharshi ni M. K et al. [8]	Identifying mango diseases	Deep learning technique	Leaf	Not reported
Dhameliya S.et al. [9]	Volume estimation of mango	computer vision system	Fruit	80%
Prakash B. and Yerpude A. [10]	Identifying mango diseases	Back Propagation Neural Network	Leaf	94%
Elqassas R. and Abu-Naser S.S. [11]	Detection of mango diseases	Expert system	Fruit	Not reported
Sethupathy J. and Veni S. [12]	Identifying mango diseases	Support Vector Machine, Artificial Neural Network	Leaf	Not reported
S. B. Ullagaddi and S.Viswanadha Raju[14]	Diagnose of pathological problems in mango	Wavelet-based principal component analysis, rotating kernel transform with artificial neural network	Flower Fruit Leaf	98.50%, 98.75%, 98.70%
	Detection of mango diseases	Deep learning neural network	Leaf	91%

Sampada Gulavnai and Rajashri Patil [15]				
S. B. Ullagaddi and S.Viswanadha Raju[16]	Detect black spots disease	Artificial neural network	Leaf and fruit	98%
Amritha S Nadarajan and Thamizharasi A. [17]	Detection of bacterial disease	Color features with a template matching algorithm	Fruit	Not reported
VaniAshok and D.S.Vinod[18]	Detect Defects in mango	Textural features with neural network	Fruit	90.1%
Maqbool I. et al. [19]	Identify Mango Leaves	Shape, morphological features artificial neural network	Leaf	96% to 98%
Lakshmi Dutta and Tapan Kumar Basu.[20]	Classify mango trees	Geometrical features with artificial neural network	Leaf	Not reported
Abbas Q. et al. [21]	Classify mango	Principal Component Analysis, Linear/ Nonlinear Discriminant Analysis techniques	Fruit	83%
Behera S.K. et al. [22]	Classify mango	Statistical Feature and Multi class support vector machine	Fruit	90%
Yossy E.H. et al. [23]	Mango sortation	Computer vision and artificial neural network	Fruit	94%
Chhabra M. et al. [24]	classify ripe / unripe mango	geometric, morphological features with neural network	Fruit	95.5 %

Zheng H. and Lu H. [25]	Classify browning mango	Fractal dimension, least square support vector machine	Fruit	85.19% to 88.89%
Nandi C.S. et al. [26]	Mango sorting	Support vector machine and Recursive features elimination method with Machine Vision	Fruit	96%
Tomas U. Ganiron Jr. [27]	Mango sorting	Area, perimeter, percent defect and roundness with nearest neighbor technique	Fruit	Not reported
Denchai W. et al. [28]	Predict the ripeness of mangoes at harvest	of biochemical, physical, and electrical properties, green color, weight, red color, TSS, blue color, TSS-TA ratio, weight and capacitance ratio, TA, voltage, capacitance with Machine Learning Methods	Fruit	The GNB, and SVM, and FANN models had average accuracies of 73.0%, 75.0%, and 85.0%, respectively
A. B. Alejandro et al. [29]	Grad and Sort mangoes	Color, black spots and area with probabilistic neural network	Fruit	87.5%
P. Borianne [30]	Identify and detect mango	Faster R-CNN network	Trees	90% for detection 56% for identification
A. S.A. Mettleq [31]	Classify mango	CNN	Fruit	100%
N.T.Thinh [32]	Sort and Classify	AI	Fruit	Not reported
V. Bhole[33]	Classification	CNN	Fruit	92.27 %
A. M. Vyas [34]	Grading	Color, size features with Ten grading rules	Fruit	94.97%
S. Girish [35]	Classification	CNN	Fruit	97.6%

M. K.Tripathi [36]	Grading	CNN	Fruit	92%
D. Worasawate. et al. [37]	Classification	machine learning	Fruit	89.6%
H. M. R. Iqbal and A. Hakim [38]	Classification and Grading	CNN	Fruit	99.2% classification and 96.7% grading

3. Weaknesses and Challenges

Most researchers use images of fruit or leaf with a plain background, while few use images of whole mango trees or images with a complex background [14,16]. An extra effort needs to be made on extracting mango images from trees or video movie. Researches [12,20,23] need to increase number of images in order to improve classification accuracy. Most researchers based on images taken from the internet or by using a digital camera, while it is better to use a scientific database to get better results. Distinguishing mango from another based on their shape is a challenge because most mango fruits are different in size, color, and even shape from one country to another, and sometimes even in the same country. So, it is better to adopt additional features with shape features. Some of approaches using deep learning or neural network to improve the performance of classification by modified number of nodes or number of neural layers, this is challenging, how to find out the ideal number of nodes and layers. It is important to have good experiences for choosing correct values for nodes and layers. In [26] the algorithm takes a long training time and misclassification happen when black spot appears on mango. In [27] mis-identification of the stem was occurred since it can be brown or green. The green stem represents healthy whereas the brown stem represents defective. In [30] the cross validations explained the need to pledge extra improvements to make the predictions of the R-CNN more pertinent to users' ambition. Some studies did not mention details of: image collection or database used [6,19], accuracy rate of their work [6,8,11,17,20,27,32]. Approaches [9,21,25,28,29] need to increase number of key parameters to improve accuracy rate.

4. Conclusion.

This paper reviewed the various techniques of mango diseases identification, mango classification. New researchers can base on this review to make a comparison between their results and the previous results. Number of methods were discussed for pre-processing stage: resizing, grayscale and binary image transformation, scaling, noise removing, image morphology processes, edge detection, segmentation, erosion/dilation and boundary tracing. Digital camera is used to capture images, most approaches used single digital camera whereas one approach is used two cameras. Most mango grading and sorting automated systems are based on mango fruit whereas mango diseases detection systems based on leaves of the mango. In feature extraction stage features are classified into: textural features, shape features, rst-invariant features, color features, geometric features and morphological. Textural

features, shape features, and color features are the most commonly used. In classification stage neural network, support vector machine, machine learning, deep learning algorithms, faster R-CNN network, CNN, probabilistic neural network, and computer vision were used. Wavelet-based principal component analysis with artificial neural network and CNN achieved high accuracy of 98.75%, 100% respectively whereas GNB and SVM methods achieved low accuracy of 73.0%, 75.0% respectively.

ACKNOWLEDGMENTS

The author would like to thank Mustansiriyah University ([www. uomustansiriyah.edu.iq](http://www.uomustansiriyah.edu.iq)) Baghdad-Iraq for its support in the present work.

References

- [1] J. C. Vieccelli, D. L. De Siqueira, W. M. D. S. Bispo and L. M. C. Lemos, Characterization of Leaves and Fruits of Mango (*Mangifera Indica* L.), *Revista Brasileira De Fruticultura*, (2016), vol. 38, pp. 1-7.
- [2] D. Yadav and S. Singh, Mango: History origin and distribution, *Journal of Pharmacognosy and Phytochemistry*, (2017), vol. 6, pp.1257-1262.
- [3] W.M. Haggag, Mango diseases in Egypt, *Agriculture and Biology Journal of North America*, (2010), vol. 1, pp.285-289.
- [4] N. Sutrodhor, M. R. Hussein, M. M. Firoz, P. Karmokar and T. Nur, Mango Leaf Ailment Detection using Neural Network Ensemble and Support Vector Machine, *International Journal of Computer Applications*, (2018), vol.181, pp.31– 36.
- [5] M. S. Aboalarbe and A. Adl, Detection of mango leaf spots and mealybugs diseases using deep learning ConvNet” and LinearSVC, *International Pre-Conference Workshop on Microbial Ecology & Eco Systems*, Egypt. June 2018.
- [6] S. R. Kumar and S. Sowrirajan, Automatic Leaf Disease Detection and Classification using Hybrid Features and Supervised Classifier, *International Journal of Advanced Research in Electrical, Electronics and Instrumentation Engineering*, (2016), vol. 5, pp.4556-4563.
- [7] S. S. Veling, R. S. Kalelkar, L.V. Ajgaonkar, N. V. Mestry and N.N. Gawade, Mango Disease Detection by using Image Processing, *International Journal for Research in Applied Science & Engineering Technology (IJRASET)*, (2019), vol.7, pp.3717-3726.
- [8] M. K. Priyadharshini, R. Sivakami and M. Janani, Sooty Mould Mango Disease Identification Using Deep Learning, *International Journal of Innovative Technology and Exploring Engineering (IJITEE)*, (2019), vol.8, pp. 11-16.
- [9] S. Dhameliya, J. Kakadiya and R. Savant, Volume Estimation of Mango. *International Journal of Computer Applications*, (2016), vol. 143.
- [10] B. Prakash and A. Yerpude, Identification of Mango Leaf Disease and Control Prediction using Image Processing and Neural Network, *International Journal for Scientific Research & Development (IJSRD)*, (2015), vol. 3, pp.794-799.
- [11] R. Elqassas and S. S. Abu-Naser, Expert System for the Diagnosis of Mango Diseases. *International Journal of Academic Engineering Research (IJAER)*, (2018), vol. 2, pp.10-18.
- [12] J. Sethupathy and S. Veni, OpenCV Based Disease Identification of Mango Leaves, *International Journal of Engineering and Technology (IJET)*, (2016), vol. 8, pp.1990-1998.
- [13] D. P. Hughes and M. Salathe, an open access repository of images on plant health to enable the development of mobile disease diagnostics, [Online]. Available: <https://doi.org/10.48550/arXiv.1511.08060>.
- [14] S. B. Ullagaddi and S.V. Raju, An Enhanced Feature Extraction Technique for Diagnosis of Pathological Problems in Mango Crop, *IJ. Image Graphics and Signal Processing*, (2017), vol. 9, pp.28-39.
- [15] S. Gulavnai and R. Patil. Deep Learning for Image Based Mango Leaf Disease Detection, *International Journal of Recent Technology and Engineering (IJRTE)*, (2019), vol. 8, pp.54-56.
- [16] S. B. Ullagaddi and S. V. Raju, Disease Recognition in Mango Crop Using Modified Rotational Kernel Transform Features, *International Conference on Advanced Computing and Communication Systems (ICACCS)*, Coimbatore, INDIA, Jan. 06 – 07, 2017.
- [17] A. S. Nadarajan and A. Thamizharasi, Detection of Bacterial Canker Disease in Mango Using Image Processing, *IOSR Journal of Computer Engineering (IOSR-JCE)*, (2017), vol.1, pp.901-08.

- [18] V. Ashok and D.S. Vinod, A Comparative Study of Feature Extraction Methods in Defect Classification of Mangoes using Neural Network, 2nd International Conference on Cognitive Computing and Information Processing (CCIP), India, 2016.
- [19] I. Maqbool, S. Qadri, D. M. Khan and M. Fahad, Identification of Mango Leaves by Using Artificial Intelligence, International Journal of Natural and Engineering Sciences, (2015), vol. 9, pp.45-53.
- [20] L. Dutta and T. K. Basu, Extraction and Optimization of Leaves Images of Mango Trees and Classification Using Ann, International Journal of Recent Advances in Engineering & Technology, (2013), vol. 1, pp.46-51.
- [21] Q. Abbas, M. M. Iqbal, S. Niazi, M. Noureen, M. S. Ahmad, M. Nisa and M. K. Malik, Mango Classification Using Texture & Shape Features, IJCSNS International Journal of Computer Science and Network Security, (2018), vol.18, pp.132-138.
- [22] S. K. Behera, S. Sangita, A. K. Rath and P. K. Sethy, Automatic Classification of Mango Using Statistical Feature and SVM, Advances in Computer Communication and Control, (2019), vol. 1, pp.469-475.
- [23] E. H. Yossy, J. Pranata, T. Wijaya, H. Hermawan and W. Budiharto, Mango Fruit Sortation System using Neural Network and Computer Vision, 2nd International Conference on Computer Science and Computational Intelligence ICCSCI, Indonesia, 2017.
- [24] M. Chhabra, A Gupta, P. Mehrotra and S. Reel, Automated Detection of Fully and Partially Riped Mango by Machine Vision, Proceedings of the International Conference on SocProS, 2012.
- [25] H. Zheng and H. Lu, "A least-squares support vector machine (LS-SVM) based on fractal analysis and CIELab parameters for the detection of browning degree on mango (*Mangifera indica* L.)", J. Comp. and Electr, (2012), vol. 83, pp.47-51.
- [26] C. S. Nandi, B Tudu and C. Koley, A Machine Vision-Based Maturity Prediction System for Sorting of Harvested Mangoes, IEEE transactions on instrumentation and measurement, (2014), vol. 63, pp.1722-1730.
- [27] T. U. G. Jr, Size Properties of Mangoes using Image Analysis, International Journal of Bio-Science and Bio-Technology, (2014), vol. 6, pp.31-42.
- [28] L. Agilandeewari, M. Prabukumar and S. Goel, Automatic Grading System for Mangoes Using Multiclass Svm Classifier, International Journal of Pure and Applied Mathematics, (2017), vol. 116, pp.515-523.
- [29] A. B. Alejandro, J. P. Gonzales and J. P. C. Yap, Grading and sorting of Carabao mangoes using probabilistic neural network, AIP Conference Proceedings, (2018), vol. 2045, pp.1-6, <https://doi.org/10.1063/1.5080878>.
- [30] Philippe Borianne, Julien Sarron, Frédéric Borne, Émile Faye, Deep Mangoes: from fruit detection to cultivar identification in colour images of mango trees, DISP'19 International Conference on Digital Image and Signal Processing, (2019), pp. 1-8, DOI: <https://doi.org/10.48550/arXiv.1909.10939>
- [31] A. S. A. Mettleq, I. M. Dheir and A. A. Elsharif, Classification of Mango Using Deep Learning, International Journal of Academic Engineering Research (IJAER), (2019), vol. 3, pp.22-30.
- [32] N. T. Thinh, N. D. Thong and H. T. Cong, Sorting and Classification of Mangoes based on Artificial Intelligence, International Journal of Machine Learning and Computing, (2020), vol.10, pp. 374-380, <http://doi:10.18178/ijmlc.2020.10.2.945>.
- [33] V. Bhole and A. Kumar, Mango Quality Grading using Deep Learning Technique: Perspectives from Agriculture and Food Industry, Association of Computing Machinery SIGITE'20, (2020), pp. 180-186, <https://doi.org/10.1145/3368308.3415370>.
- [34] S.Naik, B. Talati and S. Naik, Quality Inspection and Classification of Mangoes using Color and Size Features, International Journal of Computer Applications, (2014), vol. 98, pp.1-5, <http://DOI: 10.5120/17144-7161>.
- [35] S. Girish, K J. Shetty, D. Krithi, M. K. Kalkur and A. Megha, Mango Classification for Agro-based Industries using Transfer Learning Technique, International Journal for Research in Applied Science & Engineering Technology (IJRASET), (2020), vol.8, pp.1042-1047.
- [36] M. K. Tripathi and D. D. Makedtar, Optimized deep learning model for mango grading: Hybridizing lion plus firefly algorithm, IET Image Processing, (2021), vol. 15, pp.1940-1956, <http://DOI: 10.1049/ipr2.12163>.
- [37] D. Worasawate, P. Sakunasinha, and S. Chiangga, "Automatic Classification of the Ripeness Stage of Mango Fruit Using a Machine Learning Approach", Agri Engineering, (2022), vol. 4, pp.32-47, <https://doi.org/10.3390/agriengineering4010003>.
- [38] H. M. R. Iqbal and A.Hakim, "Classification and Grading of Harvested Mangoes Using Convolutional Neural Network", International Journal of Fruit Science, (2022), vol. 22, pp.95-109, <https://doi.org/10.1080/15538362.2021.2023069>.