Synthesis of Si Nanoparticles by Milling Technique

Khawla S. khashan 🕞

University of technology, Department of Applied Sciences/Baghdad Email:Khawla salah@yahoo.com

Revised on: 16/5/2012 & Accepted on: 9/5/2013

ABSTRACT

Silicon (Si) nanoparticles which studied are in the size range (7 – 23 nm) have been synthesized by mechanical milling. The milled powder was etched by HF & CH₃COOH acids. The size, structural, and optical characterization of these nanoparticles were determined by X-ray diffraction(XRD), Atomicforce microscopy (AFM), Fourier transform infrared spectroscopy (FTIR) and UV-VIS spectroscopy. The result confirmed that Si isnanoparticles in crystal phase with band gap 3.15eV, due to the effect of quantum confinement. This technique has been shown to have an advantage over other methods of producing nanoparticles because of low cost, small particles size, low agglomeration, narrow size distributions and uniformity of crystal structure and morphology.

Keywords: Si Nan particles, Mechanical Milling, FTIR, Optical Band Gap.

انتاج جسيمات السيلكون النانوية بتقنية الطحن الميكاني

لخلاصه

تم دراسه تحضير الجسيمات النانويه من السيلكون والتي هي بحجم يترواح من (7 – 23 nm بطريقه الطحن الميكانيكيه. تم اظهار المسحوق المطحون بواسطة الاحماض KRD) و مجهر القوى حددت الخصائص البصريه والتركيبيه والحجمباستخدام حيود الاشعه السينيه (XRD) و مجهر القوى الذريه (AFM) وتحويل فورييه الطيفيه تحت الحمراء (FTIR) والتحليل الطيفي للاشعه المرئيه وفوق البنفسجيه (UV-VIS). أكدت النتيجة أنالجسيمات النانويه من السيلكون Si هي بالطور البلوري مع فجوه طاقه Ve 3.15 و يرجع ذلك إلىتأثير الحصر الكمي. وقد تبين أنهذه التقنية لديها مزايا أكثر منغيرها من أساليبانتاج الجسيمات النانويه من حيث انخفاض الكلفه وحجم الجسيمات الصغيره وتجانس التركيب البلوري وطبيعه السطح.

INTRODUCTION

anoparticles of many materials have received great attention lately, as researchers have become increasingly aware that reducing the size of materials to the nanometer scale can change their properties in fundamental ways, thus generating attractive electronic, optical, magnetic, and catalytic properties associated with their nanoscale or quantum scale dimensions [1]. Following the discovery of electrochemically etched nanoporous silicon by Canham and co-workers [2], a great deal of research has been performed on producing nanosized Si with visible photoluminescence and on characterization of its structure and optoelectronic properties [3, 4].

This luminescence from nanosized Si has been attributed to radiative recombination of carriers confined in Si nanoparticles, and its color can be modified from blue to red by changing the nanoparticles size. One benefit of exploiting the optical properties of silicon nanoparticles over other materials is the potential of silicon nanoparticles to be integrated within existing silicon technologies in order to create nanoscale optoelectronic devices. These applications include their use as chemical sensors [5], optoelectronic devices [6], solar cell [7], photo-detectors [8], and as fluorescent biomarkers [9].

Many methods have been developed for the synthesis of nanoparticles, including laser pyrolysis [10], sputtering [11], micro-emulsion [12] and chemical vapor deposition [13]. All these techniques have a common difficulty that the ultrafine particles cannot be produced in large scale. Unlike the above methods, mechanical attrition can easily produce nanocrystalline materials up to industrial quantities; mechanical attrition by ball milling has been a popular method to make nanocrystalline because of its simplicity to essentially all classes of materials [14]. In this technique starting powder particles are trapped between highly kinetic colliding balls and the inner surface of the vial, which causes repeated deformation, rewelding, and fragmentation of premixed powders resulting in the formation of fine, dispersed particles in the grain refined matrix[15].

In this work, synthesis of Si nanoparticles using ball milling technique studying andtheir structural and optical properties had been done. Structure and morphology properties are studied by using X-ray diffraction (XRD), and atomic force microscopy (AFM), while optical properties were studied using UV-visible absorption and Fourier transform infrared (FTIR) spectroscopy.

EXPERIMENT

Commercially available Si- wafer was used as the starting material. The Si- wafer was milled in a mechanical milling machine at 300 rpm for twohours in a stainless steel vial under atmospheric pressure and temperatureusing stainless steel balls of 6 mm diameter. Aftermilling, this powder was etched with solution of CH₃COOH and HF in water to reduce the particle size. After etching, the particles were washed with water and methanol, finally they were collected by filtration using Teflon filter. In order to study the structural of Si nanoparticles we performed that using X- ray diffract meter (Philips, PW/1710), with monochromatised CuK α radiation of wavelength 0.15418nm at 40 KV and 30mA. An AFM (Advance angstrom Inc. SPM AA3000) was used to study the particles size and morphologyof millednanoparticles NPs. A small portion of powder dispersed in DMSO (diethyl sulphoxide) and ultrasonically was used to record UV-VIS absorption spectrum.

Optical properties of the NPs were studied using UV-visible absorption, which recorded by employing a Cecile-7200 double beam UV/VIS spectrophotometer supplied by Aquarius Company for the wavelength range of 200-1100 nm. While Fourier transform infrared FTIR spectrophotometer (IR Affinity-1, SHIMADZU) was used to study surface chemical composition of NPs in the range of 400-4000 cm⁻¹. KBr pellet was employed for the powder.

RESULTS AND DISCUSSION

Figure (1) shows an x-ray pattern of prepared silicon nanoparticles, there are three main sharp peaks at $2\theta = 28.3^{\circ}$, 47.1° , and 56.1° , which are characteristic of nanocrystalline silicon,these corresponding to the structures(111), (220) and (311), which confirms high crystalline nature respectively, while broad amorphous peak is present around $2\theta = 20^{\circ}$. The XRD data agree well with Li *et al* [16] results of the prepared Si nanoparticle by laser induced pyrolysis and Dhara*et al* [17] results of prepared Si nanoparticles by ball milling.

The chemical composition of the particles was examined using FTIR spectroscopy. An FTIR spectrum is shown in Figure (2), the broad absorption band with a peak of 3200–3500 cm⁻¹ and the peak at 1631.7 cm⁻¹ are due to stretching and deformation of OH vibrations. The peak appeared at 2862.2 cm⁻¹ corresponds to stretchingof C–H vibrations. A broad band in the spectral area of 1350–1550 cm⁻¹ isdue to deformation of C–H vibration. While Si-O and Si-O-Si bond stretching peaks around 459 cm⁻¹,1087.8 cm⁻¹ are observed. Peaks around 609.5 cm⁻¹ and 2335.6 cm⁻¹, are due to the hydrogenated surface, related to Si-H vibration. The peak at 678.2 cm⁻¹ can be attributed to the Si-Si stretching mode; these results were agreement with result in reference [17-19].

The Si-O bonds in the sample presumably come from slow air oxidization, since the particles are prepared in an oxygen-free environment and their as-prepared surfaces could consist of a mixture of H - termination and dangling bonds. While the Si-H, C-H, OH bonds were come from Washing with water and methanol as the final step in the etching procedure. Clearly, the state of the particle surface changes substantially during the etching process [17].

Figure (3) shows AFM image for Si NPs (image size 1000nm x 1000nm), figure (3b) shows the histogram of size distribution of Si nanoparticles with size ranging from (7-23 nm). While figure 4 showsabsorption spectra of Si nanoparticles, the absorption is high at UV range and decrease in the visible range. Also shows there absorption peak at about 525nm shifted of absorption edge are expected due to change in nanoparticle size which is quantum confinement effect [20]. As the mean particle size decreased, it was observed that the intensity of absorption increased and also leads to widening of the band gap [21], However, the spectra are not showing the smooth curves due to the shape of the particle which are not uniform and not monodispersed. The shape of the particle also affects the shifts of the wavelength[18]. From the transmission data, nearly at the fundamental absorption edge, the values of absorption

coefficient α are calculated in the region of strong absorption using the following equation [22]:

$$\alpha = \frac{1}{t} \ln \left(\frac{1}{T} \right) \qquad \dots (1)$$

The energy gaps E_g of Si nanoparticles was estimated using Tauc relation [22, 23]:

$$\alpha h v = A(hv - E_a)^{1/2} \dots (2)$$

Where:

 E_g = the band gap energy.

 α = the absorption coefficient.

A= constant.

hv = The photon energy.

The band gap was determined from Figure (5), the $(\alpha h v)^2$ isplotted as a function of the photon energy hv. Silicon nanoparticles synthesized here are direct band gap semiconductors [23]. From the data plotted in figure 5the bandgap energy is determined by using linear extrapolation. The obtained band gap energyof Si nanoparticles is E_g =3.15eV which corresponding to a blue shift of 2.03eV from the band gap of E_0 =1.12 eV of bulk Si due to the effect of quantum confinement. Also, the extinction coefficient k can be calculated by the following equation [22]:

$$K = \frac{\alpha \lambda}{4 \pi} \qquad \dots (3)$$

Figure(6), shows the variation of extinction coefficient with wavelength, excitation coefficient related to attenuation value of electromagnetic wave where its passed through the medium, so that the high value of short wavelength related to the loss incident energy in absorption process or due to loss the wave in electron transit between the energy level but this result is revere in long wavelength this is may be related to appear another absorption process such as absorption by charge carrier.

CONCLUSIONS

Si nanoparticles have been synthesized by mechanical milling. The Si NPs were investigated using XRD, AFM, UV-visible and FTIR.X-ray diffraction patterns revealed that the Si NPs have crystal structure, with size in the range (7-23nm). The band gap energy of Si nanoparticles is Eg=3.15eV, which obtained from absorption spectra. The dispersion spectra of α and kalsoobtained from the transmission data. FTIR spectra show chemical composition Si NPs. This technique has been shown to have advantages over other methods of producing nanoparticles in terms of low cost, small particle sizes, low agglomeration, narrow size distributions and uniformity of crystal structure and morphology.

REFRENCE

- [1]. Niemeyer, C. M. "Nanoparticles, Proteins, and Nucleic Acids: Biotechnology Meets Materials Science "Angew. Chem., Int. Ed. 40, 4128(2001).
- [2].Canham L. T. "Silicon quantum wire array fabrication by electrochemical and chemical dissolution of wafers" Appl. Phys. Lett. 57, 1046 (1990).
- [3].Lu, Z H, Lockwood D J, &Baribeau JM. "Quantum confinement and light emission in SiO₂/Si superlattices"Nature 378, 258(1995).
- [4].Heath, J. R "A Liquid-Solution-Phase Synthesis of Crystalline Silicon" science 258, 1131(1992).
- [5].Kelly M.T.&A.B. Bocarsly. "Mechanisms of photo luminescent quenching of oxidized porous silicon applications to chemical sensing" Coordination Chem. Rev. 171, 251(1998).
- [6].Löper P, Hiller D, Janz S, Hermle M,Glunz S W ,& Zacharias M. "Optoelectronic properties of Silicon quantum dots" Presented at the 23rd Workshop on Quantum Solar Energy Conversion, 20-26 March, Bad Hofgastein, Austria, (2011)
- [7].Nalini R. P., Dufour C., Cardin J., &Gourbilleau F." New Si-based multilayer for solar cell applications"Nanoscale Research Lett. 6,156(2011).
- [8].KonleJ. ,PrestingH. , Kibbel H., Thonke K., Sauer R. "Enhanced performance of silicon based photo detectors using silicon/germanium nanostructures" Solid state electron. 45, 1921(2001).
- [9]. Wang L., ReipaV., Blasic J.," Silicon nanoparticles as a luminescent label to DNA"Bioconjug. Chem. 15, 409(2004).
- [10].BorsellaE., Amato R., Terranova G., FalconieriM., Fabbri F. "Synthesis of nanoparticles by laser pyrolysis: from research to applications" Contribution to the Italy in Japan 2011, initiative Science, Technology and Innovation, Energia, AmbienteInnovazione (EAI), 4-5:54(2011).
- [11].Zhu Y, Wang H,&Ong P P. "Strong and stable photoluminescence from sputtered silicon nanoparticles" J. Phys. D: Appl. Phys. 33, 1965(2000).
- [12].LiongW. L.,SreekantanS.,&Hutagalung S. D." Effect of Concentration of Sodium Borohydrate on the Synthesis of Silicon Nanoparticles via Microemulsion Route" World Academy of Science, Eng. Tech. 59,419(2009).
- [13].Kumar A., Agarwal P. B., Kumar S., Joshi B.C., Sharma A.K., & Chander H." Low-pressure Chemical Vapour Deposition of Silicon Nanoparticles: Synthesis and Characterisation" Defence Sci. J., 58, 550(2008)
- [14].Lam C., Zhang Y.F., Tang Y.H., Lee C.S., Bello I., Lee S.T. "Large-scale synthesis of ultra fine Si nanoparticles by ball milling"J. Crystal Growth. 220 .466(2000)
- [15].Salah N., HabibS S, Khan Z H, MemicA, AzamA,AlarfajE,ZahedN , Al-HamediS." High-energy ball milling technique for ZnOnanoparticles as antibacterial material "Inter. J. Nanomedicine6,863(2011)
- [16].Li X., He Y., Talukdar S. S., and Swihart M. T. "Process for Preparing Macroscopic Quantities of Brightly Photoluminescent Silicon Nanoparticles with Emission Spanning the Visible Spectrum" Langmuir19, 8490 (2003)

- [17].Dhara S. and GiriPK "Size-dependent visible absorption and fast photoluminescence decay dynamics from freestanding strained silicon nanocrystals" Nanoscale Research Letters 6,320(2011).
- [18].Heintz A. S., Fink M. J. and Mitchell B. S. "Silicon nanoparticles with chemically tailored surfaces" Appl. Organometal. Chem. 24,236 (2010)
- [19].Li Z. F., Swihart M. T., and Ruckenstein E. "Luminescent Silicon Nanoparticles Capped by Conductive Polyaniline through the Self-Assembly Method" Langmuir 20, 1963 (2004)
- [20].Liu Q., KauzlarichS. M. "A new synthetic route for the synthesis of hydrogen terminated silicon nanoparticles" Mater. Sci. Engine. B96, 72(2002).
- [21].KaleleS., GosaviS. W., Urban J., KulkarniS. K. "Nanoshellparticles:synthesis, properties and applications" Current Sci. 91, 1038(2006).
- [22].Sze S.M.," Physical of semiconductor devices "Wiley –inter science publication, New York(1983).
- [23].Meier C.,GondorfA., Lüttjohann S., and Lorke A. "Silicon nanoparticles: Absorption, emission, and the nature of the electronic bandgap " J. Appl. Phys. 101, 103112 (2007).




Figure (1) X-ray diffraction (XRD) pattern for Si nanoparticles.




Figure (2) FTIR spectra of Si nanoparticles.




Figure (3) AFM image (1000nm x 1000nm): a) Two dimensional (2D) image for Si nanoparticles.b) Histogram of Si nanoparticles size distributions.




Figure (4) Absorption spectra of Si nanoparticles.




Figure (5) T_{auc} plot from the absorption spectra obtained for Si nanoparticles.




Figure (6) Variation of extension coefficient vs. wavelength for Si nanoparticles.