

KUFA JOURNAL OF ENGINEERING ISSN 2071-5528 PRINTED IN IRAQ

## NUMERICAL MODELING OF MIXED CONVECTION HEAT TRANSFER OF LAMINAR FLUID IN RECTANGULAR ENCLOSURE WITH OPENINGS IN THE SIDE

Assist Lecturer: Angam Fadil Abed College of Engineering, University of Kufa Email-engang2012@yahoo.com (Received:10/6/2010; Accepted : Feb./2012)

#### ABSTRACT

An analysis of mixed convection heat transfer inside a rectangular enclosure with side openings was numerically examined. The fluid enters the enclosure through an opening in the left vertical wall and exits from another opening placed in the right vertical wall. Two-dimensional Navier-Stockes equations are solved by using control volume based finite element technique .For mixed convection, the significant parameters are Grasfof number, Richrason number, and Reynolds number by which different fluid and heat transfer characteristics inside the enclosure are obtained. Streamlines, isotherms, average Nusselt number ,maximum temperature and other parameters of the heated wall are reported in the present study for Ri=0 to 10,Re=50,100,500,1000,Pr=0.7 to 100 and different aspect ratios. The computational results indicate that the heat transfer coefficient is strongly affected by Reynolds number and Richarson number. Higher Nusselt number is observed at large value of Pr. The comparison of the present results has been made are found in good agreement with known results.

Keyword: numerical, Natural convection, heated plate.

النمذجة العددية لانتقال الحرارة بالحمل المختلط لمائع طباقي في حيز مستطيل ذو

فتحات في جانبه

م.م. انغام فاضل عبد جامعة الكوفة / كلية الهندسة

الخلاصة:

في هذه الدراسة، تم تحليل انتقال الحرارة بالحمل المختلط في وسط مغلق مستطيل الشكل بوجود فتحات جانبيه بصوره عديه. يدخل المائع عن طريق فتحه موجودة في الجدار العمودي الأيسر للوسط المغلق و يغادر من خلال فتحه أخرى في الجدار العمودي الأيمن. تم استخدام معادلات نفير حستوك ببعدين وباستخدام تقنية الحجوم المحددة.العوامل المؤثرة في الحمل المختلط هي رقم كريشوف، ورقم رينولدز ورقم ريكار دسون.وقد تم الحصول على خواص حرارية مختلف للمائع داخل الوسط منها خطوط الانسياب،خطوط درجات الحرارة الثابتة، رقم نسلت،اكبر درجة حرارة و معاملات أخرى للجدار المسخن .وقد تم استخدام مدى واسع لهذه المعاملات ( 0=R1 الى 100, 1000, 1007, 1007 الى 1000) و عند نسبة عرض الى طول مختلفة.وقد بينت الحسابات ان معامل انتقال يتأثر بصوره كبيره برقم رينولدز ورقم ريكار دسون،حيث وجد ان اكبر قيمه لرقم نسلت تكون عند قيم عدد برانتل كبيره. وقد قورنت النتائج لهذه الدراسة مع الدراسات السابقة ووجد تطابق جيد. الكلمات الدلالية : عدى ، حمل طبيعى ، صفيحة مسخنة .

g	gravitational acceleration $(ms^{-2})$	Т	temperature (K)			
Α	Aspect ratio(D/H)	θ	non-dimensional temperature, $(T-T_i)/(q H/k)$			
Gr	Grashof number, $g\beta qH^4/v^2 k$	$\theta_{max}$	Maximum non-dimensional temperature			
h	convective heat transfer coefficient $(Wm^{-2}K^{-1})$	<i>u</i> , <i>v</i>	velocity components (ms <sup><math>-1</math></sup> )			
k	thermal conductivity of the fluid $(Wm K^{-1})$	U, V	non-dimensional velocity components, u/ui, v/vi			
Н	Height of the vertical sidewall of the enclosure (m)	Ui	Inlet velocity			
hi	Hight of inflow and outflow openings	х, у	Cartesian coordinates (m)			
D	Width of the enclosure	Х, Ү	non-dimensional Cartesian coordinates, x/H,y/H			
$D_{_{H}}$	length of the heated wall					
Nu <sub>a</sub>	Average Nusselt number	Greek symbols				
Ν	non-dimensional distance	α	thermal diffusivity, $k/\rho C_p(m^2 s^{-1})$			
р	pressure $(Nm^{-2})$	β	thermal expansion coefficient $(K^{-1})$			
Р	non-dimensional pressure	ρ	density of the fluid (kg $m^{-3}$ )			
Pr	Prandtl number, $v/\alpha$	υ	kinematic viscosity of the fluid $(m s^{2})^{-1}$			
q	heat flux $(Wm^{-2})$	Subscripts				
Ra	Rayleigh number, Gr·Pr	i	Inlet state			
Re	Reynolds number, $u_i H/v$	Н	heated surface			
Ri	Richardson number, Gr/Re <sup>2</sup>	т	maximum			

#### NOMENCLATURE

#### Introduction

In a mixed convection, both natural convection and forced convection participate in the heat transfer process [1].Thermal buoyancy forces play a significant role in forced convection heat transfer when the velocity is relatively small and the temperature difference between the surface and the free stream is relatively large. The buoyancy force modifies the flow and the temperature fields and hence the heat transfer rate from the surface[2].Many theoretical as well as experimental studies have been made for either pure forced convection or pure free convection[3].Very little has been known about combined free and forced convection heat transfer. In reality, pure forced convection heat transfer seldom occurs since density is dependent on temperature. Mixed convection, i.e., combined free and forced convection is the most general heat transfer phenomena. Pure free and pure forced convection are only limiting cases when either type of mixing motion can be neglected in comparison to the other[4].

Arpaci and Larsen[5] have presented an analytical treatment of the mixed convection heat transfer in tall cavities which had one vertical side moving other vertical boundaries at different temperatures and horizontal boundaries are adiabatic. They showed that in this particular case, the forced and buoyancy-driven parts of the problem could be solved separately and combined to obtain the general mixed convection problem. Manca et al[6], worked out a numerical investigation of three different cases of mixed convection in a channel with an open cavity for various ratios of channel opening and cavity height and the range of the governing parameters were 0.1<Ri<100, and Re=100 and 1000.Mixed convection in enclosures with one isolated heat source, in which the interaction between an external forced flow and an internal buoyancy flow determines the fluid flow transfer received considerable and heat structures. has attention .Papanicolaou and Jaluria<sup>[7]</sup>numerically studied two-dimensional laminar mixed convection in a rectangular enclosure with a discrete heat source mounted on the wall. Ahmed M.,E.[3], studied mixed convection in vertical stationary eccentric annulus for power law fluids using finite difference analysis. The nonlinear coupled momentum and energy equations have been solved using an iterative technique to obtain the velocity and temperature profiles. The outer surface of the annulus is considered to be adiabatic, while the inner surface has a uniform temperature.

Carios et al.[8] studies combined forced and free convection heat transfer in semi porous twodimensional rectangular open cavity. The open cavity consist of two vertical walls closed to the bottom by uniform heat flux. One vertical wall is a porous wall and fluid inflows normal to it. The other wall transfers the same uniform heat flux to the cavity. They showed how natural convection effects may improve the forced convection inside the open cavity. Mixed convective is one of the preferred methods for cooling computer systems and other electronic equipments. In this paper, we investigate the problem of mixed convection in rectangular horizontal vented enclosure of different aspect ratios with a uniform constant flux heat source embedded on the bottom wall, and the other walls are insulated. The objective of this study ,is to analyze the effect of Prantl , Richardson, and Reynolds numbers on the heat transfer characteristics of laminar mixed convection.

## MATHEMATICAL ANALYSIS

We consider a rectangular enclosure of different aspect ratios with uniform constant-flux heat source(q) applied on the bottom wall. The inflow opening located on the left vertical wall and the outflow opening at the top of right vertical wall and the size of the inlet port is the same size as the exit port which is equal to hi=0.1H. The other walls are assumed adiabatic. Details of the geometry and coordinate system are shown in Fig.(1).The flow velocity of the fluid through the inflow opening is assumed to be uniform ui at constant temperature Ti .The governing equations are those expressing the conservation of mass, momentum, and energy. The flow is considered to be steady, laminar and two-dimensional. Constant thermal properties are assumed except for the density in the body force term of the y-momentum equation which is modeled by the Boussineq approximation. The governing equations for steady mixed convection flow can be written as [2]:

$$\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} = 0 \qquad \dots (1)$$

$$u \cdot \left(\frac{\partial u}{\partial x}\right) + v \cdot \left(\frac{\partial u}{\partial y}\right) = -\left(\frac{1}{\rho}\right) \cdot \left(\frac{\partial p}{\partial x}\right) + v \cdot \left[\left(\frac{\partial^2 u}{\partial x^2}\right) + \left(\frac{\partial^2 u}{\partial y^2}\right)\right] \qquad \dots (2)$$

$$u \cdot \left(\frac{\partial v}{\partial x}\right) + v \cdot \left(\frac{\partial v}{\partial y}\right) = -\left(\frac{1}{\rho}\right) \cdot \left(\frac{\partial p}{\partial y}\right) + v \cdot \left[\left(\frac{\partial^2 v}{\partial x^2}\right) + \left(\frac{\partial^2 v}{\partial y^2}\right)\right] + gB(T - T_0) \qquad \dots (3)$$
$$u \cdot \left(\frac{\partial T}{\partial x}\right) + v \cdot \left(\frac{\partial T}{\partial y}\right) = \alpha \left[\left(\frac{\partial^2 T}{\partial x^2}\right) + \left(\frac{\partial^2 T}{\partial y^2}\right)\right] \qquad \dots (4)$$

Using the following dimensionless variables[8]

$$X = \frac{x}{H}, Y = \frac{y}{H}$$

$$U = \frac{u}{u_{i}}, V = \frac{v}{u_{i}}$$

$$P = \frac{P}{\rho u_{i}^{2}}, \theta = \frac{T - T_{i}}{\frac{qH}{K}}$$
...(5)

)

The governing equations (1) to (4) reduce to non-dimensional form:

$$\frac{\partial U}{\partial X} + \frac{\partial V}{\partial Y} = 0 \qquad \dots (6)$$

$$U \cdot \left(\frac{\partial U}{\partial X}\right) + V \cdot \left(\frac{\partial U}{\partial Y}\right) = -\left(\frac{\partial P}{\partial X}\right) + \frac{1}{\text{Re}}\left[\left(\frac{\partial^2 U}{\partial X^2}\right) + \left(\frac{\partial^2 U}{\partial Y^2}\right)\right] \qquad \dots (7)$$

$$U \cdot \left(\frac{\partial V}{\partial X}\right) + V \cdot \left(\frac{\partial V}{\partial Y}\right) = -\left(\frac{\partial P}{\partial Y}\right) + \frac{1}{\operatorname{Re}}\left[\left(\frac{\partial^2 V}{\partial X^2}\right) + \left(\frac{\partial^2 V}{\partial Y^2}\right)\right] + \frac{Gr}{\operatorname{Re}^2}\theta \qquad \dots (8)$$

$$U \cdot \left(\frac{\partial \theta}{\partial X}\right) + V \cdot \left(\frac{\partial \theta}{\partial Y}\right) = \frac{1}{\text{Re Pr}} \left[ \left(\frac{\partial^2 \theta}{\partial X^2}\right) + \left(\frac{\partial^2 \theta}{\partial Y^2}\right) \right] \qquad \dots (9)$$

The dimensionless parameters are used to describe the performance of fluid flow and heat transfer characteristics are as follows: Reynolds number

$$\operatorname{Re} = \frac{u_i H}{\upsilon}$$

Grashof number for constant heat flux(q)source is

$$Gr = \frac{gBqH^4}{K\upsilon^2}$$

And Prandtl number is

$$\Pr = \frac{\upsilon}{\alpha}$$

The other two governing parameters, Richardson number and Peclet number are defined as :

$$Ri = \frac{Gr}{Re^2}$$
$$Pe = Re.Pr$$

The heat transfer calculation within the enclosure is measured in terms of the average Nusselt number at the heated wall as follows[1]:

$$Nu = \frac{1}{D_H} \int_{0}^{D_H} \frac{h(x)x}{K} dx = \frac{1}{D_H} \int_{0}^{D_H} \frac{X}{\theta_H} dX \qquad \dots (10)$$

Where  $D_H$  and h(x) are the length and the local convection heat transfer coefficient of the heated wall respectively,  $\theta_H$  is the local dimensionless temperature.

#### **BOUNDARY CONDITIONS**

On each of the computational domain boundaries, boundary conditions are required to solve the differential equations. The boundary conditions are:

 $u = u_i$ , v = 0,  $T = T_i$  at the inlet

$$\begin{split} u &= 0 \quad , v = 0 \quad , \frac{\partial T}{\partial x} = 0 \text{ at exit} \\ u &= 0 \quad , v = 0 \quad , q = -K \frac{\partial T}{\partial x} \text{ along the heated bottom wall} \\ u &= 0 \quad , v = 0 \quad , \frac{\partial T}{\partial x} = 0 \text{ along the vertical insulated walls} \\ u &= 0 \quad , v = 0 \quad , \frac{\partial T}{\partial y} = 0 \text{ along the horizontal top wall} \\ \text{Using the dimensionless variables, the boundary conditions become:} \\ U &= V = \frac{\partial \theta}{\partial N} = 0 \quad (\text{at the enclosure walls except the horizontal bottom wall}) \\ U &= 1 \quad , V = 0 \quad , \theta = 0 \text{ at the inlet} \\ \frac{\partial U}{\partial X} &= \frac{\partial V}{\partial X} = \frac{\partial \theta}{\partial X} = 0 \quad \text{at the exit} \\ U &= V = 0 , \frac{\partial \theta}{\partial Y} = -1 \quad (\text{At the heated horizontal bottom wall }) \end{split}$$

### COMPUTATIONAL PROCEDURE

The governing equations for  $(U, V, \theta)$  can be written in a common form for the (convectiondiffusion) problem as follow [9];

where the general scalar  $\boldsymbol{\Phi}$  stands for any one of the dependent variables under consideration, the diffusion coeffecient  $\boldsymbol{\Gamma}$  and the source term  $\boldsymbol{S}$  in cartesian form are listed below for each governing equation;

Continuity equation

$$\Phi = 1, \Gamma = 0, S = 0$$

Momentum equation in X-direction

$$\Phi = U, \ \Gamma = \frac{1}{\text{Re}}, S = -\frac{\partial P}{\partial X}$$

Momentum equation in Y-direction

$$\Phi = V, \Gamma = \frac{1}{\text{Re}}, S = -\frac{\partial P}{\partial X} + \frac{Gr}{\text{Re}^2}\theta$$

Energy equation

$$\Phi = \theta, \Gamma = \frac{1}{\operatorname{Re}\operatorname{Pr}}, S = 0$$

The numerical solution of the governing equations will be made according to the finite volume method, this method is based on principle of dividing the flow field to a number of volume elements, each one of them is called (control volume), After that a discretization process was carried out by integrating the general conservation equation (11) over a control volume element, where this equation will be as follow [10];

Where the coefficients  $(a_E, a_W, a_N, a_S)$  add the effect of convection between the main node (P) and the neighboring nodes (E, W, N, S) as shown in Fig.(2). After that and by following the (SIMPLE Algorithm) procedure, where the continuity equation was reformulated as a pressurecorrection equation[10]. Calculation starts with solving the (u, v) momentum equations, and subsequently this estimated velocity field is corrected by solving the pressure correction equation so that the velocity field fulfils the continuity principle. Finally, the energy equation are solved. This iteration scheme also allows the variables to be updated sequentially. This iteration sequence is repeated until convergence is achieved. Convergence was measured in terms of the maximum change in each variable during an iteration, the maximum change allowed for convergence check was (10<sup>-5</sup>). After getting the final values of all dependent variables in the flow field, calculations will be made for average Nusselt number.

#### **RESULTS AND DISCUSSION**

The numerical results are carried out for mixed convection in a rectangular vented enclosure. The effect of Re,Pr,Ri numbers, and aspect ratios on heat transfer characteristics have been presented. All these values are varied over wide ranges to study the effects on the thermal transport and fluid flow phenomena. The relative strength of the forced convection over natural convection can be judged on the base of Ri, in the mixed convection. In the case as Ri approaches to unity, the buoyancy effect becomes important. Consequently the natural convection dominates the mixed convection when Ri>1.Figure 3(a1 to a3,b1 to b3) shows streamlines and isotherm plots respectively for different values of Ri(0,1,10) for (A=1) and at (Re=100,Pr=0.7).At low Ri, buoyancy effects are weak and due to hot horizontal wall, fluids move along the heated wall and rise up forming a single cell over the main flow with clockwise rotation inside the enclosure. As, Ri increases buoyancy effects accelerated the fluid near the heated wall causing an asymmetric flow

pattern producing closer streamlines near the walls. The corresponding isotherm plots for the above cases are presented in Figure3(b1 tob3). The thermal boundary layer decreases thickness slowly as the Ri increases. This is revealed by the denser concentration of isotherms near the active corner region between the right insulated wall and the wall containing the heat source. Figure4(a1 to a3) represent streamline plots for different values of Pr(1,50,100) at (Re=500,Ri=1,A=1.5). It can be seen as Pr is increased; the fluid conductivity decreases and limits the acceleration of the near hotwall fluid to a thinner thermal boundary layer region. Therefore the corresponding decreases in velocity away from the hot wall is also reduced. The corresponding isotherm plots are presented in Figure 4(b1 to b3).As Pr increases, the thermal boundary layer decreases in thickness which can be seen by the denser dustering of isotherms close to the hot wall. The spread of isotherms at low values of Pr is due to a strong stream wise conduction that decreases the stream wise temperature gradient in the fluid. The effect of increase Re(100,500,1000) on the flow and temperature distribution was seen in Figure 5 at (A=2,Pr=10,Ri=3).Figure 5(a1 to a3) represents the streamlines plots and the corresponding temperature distribution can be seen in Figure 5(b1 to b3). It can be seen the increase in Re reduces the thermal boundary thickness and it possible since at large value of Re, the effect of gravitation force becomes negligible. The effect of varying A on the flow pattern can be seen in Figure(6). ). It can be seen that any increase in aspect ratio due to increase the appearance of convective mode The heat transfer effectiveness of the enclosure is displayed in terms of average Nusselt number values and the dimensionless maximum fluid temperature. Nusselt number as a function of Richarson number for different Reynolds numbers is shown in Figure(7). When Ri increases from 0 to 3, the average Nusselt number increases moderately at low Reynolds number, but at high Re (Re>100) the average Nusselt number increases very sharply. This behavior results from the onset of thermal instabilities and the probable development of secondary flow due to uniform heating and forced flow causes rapid mixing. For increment of Ri from 3 to 10, causes a slow increase in the average Nusselt number. The effect of varying A on average Nu along the hot wall are illustrated for different Ri in Figure(8) for a Pr of 50. As the flow develops and the bulk fluid gets heated for low Ri, the Nusselt number profiles expectedly increases as the aspect ratio increase because the heat flux wall become bigger. Thus the area for convective contribution, compared to the path for flow. There always exist a maximum Nu at (A=4) for all values of Ri whereas a minimum value is found at (A=0.5). Figure(9) present the overall heat transfer results for different values of Pr for (A=1) and different Ri. Nu increases with increasing Pr, and is due to a decrease in thermal boundary thickness with a consequent increase in the temperature gradient as Pr increase. Figure(10) helps to find the onset of the convection regime. With the increase of the heat transfer rate or fluid mixing, causes increasing of  $\theta_m$ . In the present analysis for Ri>3,  $\theta_m$  depends

strongly on Re, but is nearly invariant with Ri, keeping essentially the levels of pure natural convection. This suggests that in this range of Ri the degree of mixing is either very low or the mixing pattern is such that it does not contribute any significantly to convective heat transfer. A dominance of the mixed convective heat transfer mechanism is therefore inferred for Ri<3.Conversely it can found that for  $3 \le Ri \le 10$ , the maximum temperature tends to become independent of Ri. Figure (11) illustrate the influence of Pr on the maximum temperature distribution for various Ri. Observing the temperature profile, no significant changes occurs with the increase of Ri for low value of Pr, but for high Pr the maximum temperature increases as Ri <6 and increasing Pr has almost constant effect on  $\theta_m$  for all value of Ri>6. This is because Pr is an important parameter in the energy equation and its effects are always present independent of the magnitudes of the buoyancy source term and buoyancy induced flow acceleration.. Table (1) shows results for the pure forced convection case (Ri=0).U velocities are always higher than Velocities for all Reynolds numbers, showing that the flow is dominated by an intense lateral mixing.

### **COMPARISION**

Figure(12 a) compares the present result for Nusselt number with the result by Sumon et al.[1] for mixed convection in rectangular vented enclosure and uniform heat source on the bottom wall. The right, left, and top walls are insulted. Figure(12 b) also shows the comparison of maximum temperature between the present investigation and Summon et al.[1]. The present results has a very good agreement with the results by Sumon et al.[1].

## **CONCLUSIONS**

The problem of mixed convection heat transfer of fluid in a two-dimensional horizontal vented rectangular enclosure with a constant heat flux source mounted on the bottom wall has been investigated numerically using a finite element technique. The main conclusions of the present study are:

1-The heat transfer results explain the importance of the non-dimensional parameters like Reynolds number and Richardson number in the natural and mixed convection regime. The effects of these parameters on the flow fields are also investigated.

2-The study encompasses a range of Re from 50 to 1000, a range of Pr from 0.7 to 100 and a range of Ri from 0 to 10.

3-The numerical solutions indicate that increasing the value of Re or Gr leads to higher heat transfer coefficient, higher heat source temperature and higher intensity of recirculation.

3-Adetial investigation of heat transfer in terms of average Nusselt number and fluid temperature has been undertaken for different values of A ,Ri ,Re, and Pr. The average Nu plotted along the variation of Richarson number indicates that the heat transfer from the heated wall increases rapidly up to Ri=3, then it increases at a very slow rate.

4-The maximum fluid temperature tends to be remains constant in the highly buoyancy dominated convection regime.

## <u>REFERENCES</u>

1-Sumson S.,Goutam S.,Mohammad A., and Quamrul I.," Combined free and forced convection inside a two-dimensional multiple ventilated rectangular enclosure"ARPN J., of Engineering and Applied Sciences,Vol.1,No.,3,October 2006.

2-Rahman M.M., Alim M.A., Mamum M.A.H., Chowed M.K., and Islam A.K.M., "Numerical study of opposing mixed convection in a vented enclosure", ARPN J., of Engineering and Applied Sciences, Vol.2, No., 2, April 2007.

3-Ahmed S.M.E.,"Mixed convection heat transfer of power-law fluids in a vertical eccentric annulus"Indian J.,Pure Appl.,Math.,31(3):227-242,March 2000.

4-Kakac S.,Saha R.K.,and Aung W.,Hand book of Single-Phase Convective Heat Transfer,Wiley,New York,Chapter 5.,(1987).

5-Arpaci V.S., and Larsen P.S., "Convection heat transfer:, Prentice-HALL, 90, 1984.

6-Manca O.,Nardini S.,Khanafer K.,and Vafai K.,"Effect of heated wall position on mixed convection in a channel with an open cavity", ,Numerical Heat Transfer,Part A.,Vol.43:259-282,2003.

7-Papanicalaou E.,Jaluria Y.,"Mixed convection from an isolated heat source in a rectangular enclousure",Numerical Heat Transfer A18,PP.,427-461.,1990.

8-Carios A., Jose R.C., and Valesca A.C., "Combined forced and free heat transfer in a semi porous open cavity", Scientific Research and Essay, Vol., 3(8), PP.333-337, ISSN 1992-2248, Academic Journals, August 2008.

9- Versteeg H. K. and Malalasekera W., "An introduction to computational fluid dynamics the finite volumes method", Longman Group Ltd, 1995.

10-Patankar and Spalding, "A calculation procedure for heat, mass, and momentum transfer in three-dimensional parabolic flow," Int. J. Heat Mass Transfer, Vol. 15, PP. 1787-1805, 1972.

Re	$U_m$	$V_m$
50	0.11794	0.11742
100	0.21756	0.19878
500	1.03001	1.02164
1000	2.02379	2.0109



Table(1) Absolute maximum values of velocities at Ri=0 as a function of Reynolds number

Fig.(1)Schematic diagram of the problem and coordinate system



Fig.(2)mesh distribution for two dimensional flow



Fig.(3)Streamlines and isothermal plot for different values of Ri at Re=100,Pr=0.7,A=1



Fig.(4)Streamlines and isothermal plot for different values of Pr at Re=500,Ri=1,A=1.5



Fig.(5)Streamlines and isothermal plot for different values of Re at Ri=3,Pr=10,A=2



(a1)



(b1)



(a2)



(b2)



(a3)

(b3)

# Fig.(6) Streamlines and isothermal plot at different A(A=1,2,4) for Re=50,Pr=50,Ri=1



Fig.(7) Variation of  $Nu_a$  with the Ri for different values of Re at Pr=0.7



Fig.(8) Variation of  $Nu_a$  with the A for different values of Ri at Re=100



Fig.(9) Variation of  $Nu_a$  with the Ri for different values of Pr



Fig.(10) Variation of  $\theta_m$  with the Ri for different values of Re



Fig.(11) Variation of  $\theta_m$  with the Ri for different values of Pr



results of Ref.[1] at Re=200