



DOI: <https://doi.org/10.25130/tjas.25.3.11>

Technique increasing depths of tillage in some characteristics by using moldboard plow

Galib, A .A .Muhaibis

Shatrah Technical College-Sothern Technical University-Iraq

*Corresponding author: ghaleb.muhaibis@stu.edu.iq

KEY WORDS:

*tractive efficiency, working depth,
tractor, productivity*

Received: 10/12/2024

Revision: 27/02/2025

Proofreading: 14/05/2025

Accepted: 05/05/2025

Available online: 30/09/2025

© 2025.This is an open access
article under the CC by licenses
[http://creativecommons.org/licenses
s/by/4.0](http://creativecommons.org/licenses/by/4.0)



ABSTRACT

One of the basic tasks in agricultural mechanization technology is to reduce energy consumption in agricultural operations, especially in tillage. Experiment was conducted in fields of Al- Bada in Iraq season 2024. This research studied, soil disturbed volum, practical productivity, and tractive efficiency. Best indicator involved three levels of tractor speeds (2.70, 3.40 ,3.78 km. hr⁻¹) and three levels of tilt depths (18, 22, 27) cm. Factorial experiments under (RCPD) with three replications was used in this study. It was verified superiority tractor velocity 3.78 km.h⁻¹ gets highest value soil disturbed volume which amounted 100.9m³.hr⁻¹ and higher practical productivity 0.813 ha.hr⁻¹ while velocity 2 .70 km.hr⁻¹ gets less tractive efficiency 63.23 %, tillage depth 18 cm gets lowest percentage of tractive efficiency 62.11%, depth tilled 27 cm by using moldboard plow gets highest value in soil disturbed volume 98.19m³.hr⁻¹ and practical productivity 0.843 ha.hr⁻¹. Interaction between tractor speed 3.78km.hr⁻¹ with tillage depth 27 cm was superior in getting the highest (S. D. V)100.9m³.hr⁻¹. practical productivity 0.907 ha.hr⁻¹ and higher tractive efficiency 72.00%.

تكنولوجيا زيادة اعماق الحراثة في بعض الخصائص باستعمال المحراث المطرحي القلاب

د. غالب عبد الكاظم محيبس
الكلية التقنية – الشطرة. الجامعة التقنية الجنوبية

الخلاصة

من المهام الأساسية في تكنولوجيا المكننة الزراعية تقليل استهلاك الطاقة في العمليات الزراعية وخاصة في أعمال الحرث. اجريت التجربة في حقول البدعة في العراق موسم 2024. تضمن البحث دراسة الصفات التالية لحجم التربة المثار والإنتاجية العملية وكفاءة السحب. أفضل مؤشر تضمن ثلاثة مستويات لسرعات الجرار (2.70، 3.40، 3.78 كم. ساعة⁻¹) وثلاثة مستويات لأعماق الحراثة (18، 22، 27) سم. تم استخدام التجارب العملية تحت تصميم القطاعات العشوائية الكاملة (RCPD) بثلاثة مكررات في هذه الدراسة. تم التحقق من تفوق سرعة الجرار 3.78 كم. ساعة⁻¹ في الحصول على أعلى قيمة لحجم التربة المثار وبلغت 100.9 م³ ساعة⁻¹ والإنتاجية العملية 0.813 هكتار. ساعة⁻¹، بينما السرعة 2.70 كم. ساعة⁻¹ حصلت على أقل كفاءة سحب 63.23 %، عمق الحراثة 18 سم حصل على أقل نسبة كفاءة سحب 62.11 %، وعمق الحراثة 27 سم وباستخدام المحراث المطرحي القلاب حصل على أعلى قيمة لحجم التربة المثار 98.19 م³ ساعة⁻¹ والإنتاجية العملية 0.843 هكتار. ساعة⁻¹. تفوق التداخل بين سرعة الجرار 3.78 كم. ساعة⁻¹ وعمق الحراثة 27 سم في الحصول على أعلى حجم تربة مثار 100.9 م³ ساعة⁻¹. الإنتاجية العملية 0.907 هكتار. ساعة⁻¹ وأعلى كفاءة سحب 72.00 %.

الكلمات الافتتاحية: السحب – عمق العمل – الجرار – الإنتاجية

INTRODUCTION

One of the important technological requirements for soil preparation equipment is that it performs many operations at different soil depths under different tractor speed loads. Determined by conditions of use for each type of this equipment. Using modern mechanization to increase agricultural production, reduce the time required and speed completion of work. (Alkaab. 2024; - Alkaab., and W. AH Al-Sheikh. 2024) some agricultural technical requirements are regulated, such as regulating different depths of plowing, working width, degree of soil disintegration and fragmentation, depending on working part of each type of tillage equipment (Abdul-Kreem, 2017; Isaak, M. (2011). Despite the many modern technologies in the field of using agricultural machinery and implement to prepare the soil for planting in order to provide suitable conditions for seed germination, it is not without side effects that may lead to compaction of the soil and poor aeration (Alsaady,2013; Ghali,2019; Azawi et al.). Choosing the appropriate machine, especially in process tillage, has a fundamental and major role in the success of any agricultural operation (Kareem and Sven, 2019; Abdullah and Rahman 2019; AL Nuaimi. 2020).

Each soil has characteristics that require the use of tillage equipment suitable for its type, and the mold board plow one of the most efficient types of plows in preparing the soil and achieving the goals of correct and successful agriculture (Al-Janobi et al., 2020). According (Silas and Raymond ,2020; Jyoti et al., 2019) mold board plow cuts lift and turns the furrow slice, buries trash and crop residue, aerates soil control weeds, provides good seed beds for better germination. It must be used at appropriate tractor speeds, depths, and soil moisture conditions. (Isaak et al., 2024; Al-Abdali, 2000) found increase tractor velocity from (2.63 ,4.79 to 6.94) km.hr⁻¹ decrease tractive efficiency because of high of slippage percentage in

high velocity. Increase tillage depths from 15,20 to 25 cm increase tractive efficiency (74.9, 78.1 to 78.9) %. Explain (Al-Ani et al., 2004) increase in the tractive efficiency values from (63.8 to 65.3 to 65.8) % when the plowing depth of the moldboard plow was increased from (15 to 20 to 27) cm traction linear force draft or pull resulting from torque applied to tractor tires. According (Kim et al.,2020; Aday and Al-Musawi 2009) the reason for this was attributed to increase in force resistance capacity which represents one component tractive efficiency. (Asae ,2003) effective productivity is actual amount of work done which would be done if not time were lost It depends on working width, practical speed, depth of plowing, and technical and organizational condition of the machines (Al-Tahan et al., 1995; Ghofran, 2022). According (Al- Hashimi ,2012) higher tractor practical speeds from 1.93, 2.99 to 4.88 cased high productivity (0.144, 0.227 to 0.376) ha. Hr⁻¹. (Jassim, 2018) explained below when working with a greater plowing depth and stabilizing tractor speed, this leads to a decrease in practical productivity, reason is due to an increase in traction force and slippage percentage, thus a decrease in productivity. Soil disturbed volume means that a lot of work has been done, and it increases with depth of tillage, and is accompanied by a higher in fuel consumption (Mankhi, 2012). In a study mentioned (Amer ,2017), superior moldboard plow in obtaining highest average practical productivity, amounting to 0.26 hectares/hr⁻¹, compared to disc plow, which obtained 0.22 hectares/hr. The reason is due to large design width of moldboard plow.

Considering the importance of great effect of practical speed tractor and different types of plowing depths on some mechanical properties of machine and soil properties to prepare suitable cultivation conditions using suitable plowing machines, the research aims to study effect of three levels of tractor speed, (2.70, 3.40 and 3.78)km.hr⁻¹ and three plowing depths of (18, 22 and 27)cm on some of studied indicators, which are the volume of soil stirred, practical productivity and tractive efficiency of using mold board plow.

Aim of this research study effect increasing depths of tillage in some characteristics by using moldboard plow.

MATERIALS AND METHODS

Field experiment was conducted in one of field Al-Bada area north of Dhi Qar Iraq season2024. Factorial experiments under complete randomized block design. with three replications in this experiment. First factor tractor velocity at three levels 2.70, 3.40 and 3.78km.hr⁻¹ on the secondary plot, three levels tillage depths, (18, 22, and 27 mm) on main plot. the research included 3*3*3= 27 experimental units. Using moldboard plow working width 75 cm and length 150 cm, width 97 cm and high plow 110cm. Limited working width by hydraulic device was controlled by using control lever. A stopwatch was used to determine the time required to cover the distance (30 m). After recording the required data, following calculations were performed to measure theoretical speed, practical speed, practical productivity, and soil disturbed volum according to the equations shown below.

Field tools were used to implement the experiment, where measurements were taken during implementation for theoretical velocity and time, and readings were taken after implementing experiment for remaining characteristics. An electronic stopwatch was used to measure time, a 10-meter measuring tape to measure the coefficients, a long ruler to measure

ground coefficients and depths, and indicators were used to know beginning and end of each replicate and to know limits of experiment.



Figure (1) mold board plow using in experiment

Studied attributes

V_t: theoretical speed km.hr⁻¹

$$V_t = \frac{D}{T_t} \times 3.6$$

D: Length of the plowing line (m)

T_t: The theoretical time without load (seconds)

$$PT = 0.1 * W_t * V_t$$

PT: Theoretical productivity (ha.hr⁻¹)

WT: design working width of the plow (m)

VT: Theoretical speed (km.hr⁻¹)

$$P..P = 0.1 * W_p * V_p * S_t$$

p.p: practical productivity (ha.hr⁻¹)(Kepner et al., 1982)

W_p: practical working width of the plow (m)

V_p: practical speed (km.hr⁻¹)

$$S.P.V = P_p * D_p$$

S.D.V: soil disturbed volume (m³.hr⁻¹)..... (Bukhari et al., 1988)

p.p: practical productivity (m³.hr⁻¹)

D.p: soil depth field (m)

Tractor specifications

Engine type	Direct injection Diesel
Number of cylinders	6
Internal cylinder diameter	100mm
Power stroke order	1-3-4-1
Maximum power	142hp
Engine revolution	2500 r.ma
Type of cooling	Water
Number of speeds	12
Origin	France
Model	2010 n

Plow specifications

Number of moldboards	3
Type	Cylindrical
Working width	75 cm
Length	140 cm
Height	110 cm
Total weight	160 kg

RESULTS AND DISCUSSION

Table 1. shows effected the tractor velocity, tilt depths, and interactions between them in soil disstuebed volum gets high value which amonted $100.9 \text{ m}^3.\text{hr}^{-1}$ in ground speed $3.78 \text{ km}.\text{hr}^{-1}$ and less value $85.5 \text{ m}^3.\text{hr}^{-1}$ in velocity $2.70 \text{ km}.\text{hr}^{-1}$, increasing velocity from 2.70 to 3.40 and then to $3.78 \text{ km}.\text{hr}^{-1}$ laed an increase in S.D.V from 85.5 to 96.2 and then $100.9 \text{ m}^3.\text{hr}^{-1}$. Because higher tractor speeds lead to less time to achvment work by using moldboard plow whith a large working depth. This supported by (Al-Badria and Al-Hadithi, 2011; Isaak, M. and Ahmed, M.A.) (2009).

Increaing tillage depths from (18,22 to 27)cm it causes an increase S.D.V from (90.6 ,94.1 to 98.1) $\text{m}^3.\text{hr}^{-1}$. Reason may be due to existence of a direct relationship between the tillage depth and the volume of soil stirred, as increasing depth leads to an increase in load on tractor, which leads to an increase in wheel slippage and thus an increase in the values of volume soil stirred volum. Interaction between velcity $3.78 \text{ km}.\text{hr}^{-1}$ and tillage depth 27 cm gets heightes value which amonted $102.5 \text{ m}^3.\text{hr}^{-1}$.

Table 1 Effect of tractor speeds, tillage depths and interactions between them in soil disturbed volum $m^3.hr^{-1}$.

Tractor speed Km.hr ⁻¹	Tillage depths (cm)			Average speeds
	18	22	27	
2.70	79.2	85.2	93.1	85.5
3.40	93.1	96.4	98.9	96.2
3.78	99.6	100.6	102.5	100.9
0.31		0.54		LSD
	90.6	94.1	98.1	Average depths

Look at (Table 2) indicators to effected tractor velocity, and tillage depths, and the interactions between them in practical productivity. Increasing velocity from 2.70 to 3.40 and 3.78 km .hr⁻¹ caused an increase in practical productivity from (0.637 to 0.772 and 0.813) ha.hr⁻¹, because increasing velocity will due to increase velocity in process tillage by used moldboard plow being one of factors in calculating practical productivity. Among the important factors that helped increase practical productivity were maintaining largest working width, highest practical speed, and reducing wasted time. This result agrees the finding by (Mankhi, 2012).

Shaw (Table 2) impact tractor velocity and tillage depths in practical productivity, as it is noted that increasing tillage depths from (18 to 22 and then to 27) cm leads to increase production from (90.6 % to 94.1 and 98.1) h ha.hr⁻¹. interaction between higher velocity 3.78 km.hr⁻¹ and depth moldboard plow 27 cm gets heights average practical productivity which amounted 0.907 ha.hr⁻¹.

Table 2 Effect of tractor speeds, tillage depth and interactions between them in practical productivity ha.hr⁻¹.

Tractor speeds km.hr ⁻¹	Tillage depths (cm)			Average speeds
	18	22	27	
2.70	0.507	0.633	0.770	0.637
3.40	0.703	0.760	0.853	0.772
3.78	0.677	0.857	0.907	0.813
0.096		N.S		LSD
	0.629	0.750	0.843	Average depths

It was verified the superiority tractor velocity 3.78 km .hr⁻¹ gets higher tractive efficiency which amonted 68.89 % while the loss value 63.23 % gets in first velocity 2.70 km.hr⁻¹ (Table 3) because increasing tactor speeds will caused increase movement resistance which lade to increase tractive force and slippage precentage which caused a decrease tractive efficiency values by using moldboard plow. This agrees with the outcomes of Al-Ani et al.,2004.

Table 3 as it is noted that using tilt depth from (18, 22 and 27) cm lead to gets tractive efficiency from(62.11, 65.89 to 68.55 %) . the interaction between tractor speed 3.78 km.hr⁻¹ and tillage depth 27 cm gets heghtes value which amonted 72%.

Table 3 Effect of tractor speeds,and tillage depths and the interactions between them in tractive efficiency %.

Tractor speeds km.hr ⁻¹	Tillage depths (cm)			Average speeds
	18	22	27	
2.7	60.00	62.67	67.00	63.23
3.4	62.33	64.33	66.67	64.44
3.78	64.00	70.67	72.00	68.89
1.40		2.43		LSD
	62.11	65.89	68.55	Average depths
		1.40		LSD

CONCLUSIONS

From the above results, groaned velocity 2.70, 3.40and 3.78 km.hr⁻¹gets effected in soil disturbed volume from 85.5 to 96.2 and then 100.9 m³.hr⁻¹ by used moldboard plow with large working width. Highest practical productivity in tractor speed 3.87 km.hr⁻¹ which amounted 0.813 ha.hr⁻¹ while the tilt depth 27 cm superior in all studied properties gets S.D.V. 98.1 m³.hr⁻¹, practical productivity 0.843 m³.hr⁻¹ and tractive efficiency 68.55%. Therefore, we recommend using a tractor speed 3.78 km.hr⁻¹ and tillage depth 27 cm by used mold board plow.

REFERENCES

Al-Abdali, O. A. Abdullah. 2000. The performance of the Massey Ferguson tractor 4260-MF with the 134 four-wheel moldboard plow and the effect of their interaction on some physical properties of the soil. M.Sc. Thesis, College of Agriculture - University of Baghdad.

Al-Ani, R. N., F. S. Al-Ani and Jawad K. E. 2004.The field performance of the Nida tractor with the moldboard plow 113. *Iraqi Journal of Agricultural Sciences*, 35(6) 175-178.

Abdul Razzaq, A.L. Jassim,.2018 Equipment and machines for plowing and smoothing soil for university printing and publishing Ministry of Higher Education and Scientific Research Iraq. Pp.40-41.

Abdullah, A. A., Abdul Rahman, M. S. (2019). Comparison between local manufactured panel ridge and conventional disc ridge throughout investigating their effects on power efficiency, draft force and actual field productivity. *Tikrit Journal for Agricultural Sciences*, 19 (1),126-141.

- Al-Badri, S. B., Hani, I. Al-Hadithi .2011 Study of some technical indicators and capacity requirements for the machinery unit of the Massey Ferguson Tractor MF - 650 with the moldboard plow. *Iraqi Journal of Agricultural Sciences* .42(1). pp.118-121
- Al – Janobi, A. Al-Hamed ,S., A boukarim ,A., & Almajhad , Y. 2020. Modeling of draft and energy requirements of moldboard plow using artificial neural networks biased on two novel variables. *Engenharia Agricola*,40. pp.363-373.
- Aday, S.H. and F.M. Al-Musawi. 2009. The relationship between the specific fuel consumption and the draft energy for different engine speeds and traction wheels ballasting. *Basrah. Journal. Agric. Sci. Iraq*. Vol. (22). No. (1).
- ASAE Standard. (2003). American society of agriculture engineers. Agricultural management data. ASAE D497.4FEB03.
- Al Nuaimi, B. A. M., Al Rijabo, S. A. A. (2020). Design and manufacture of chisel plow shares and their effect on some field performance indicators. *Tikrit Journal for Agricultural Sciences*, 20 (1), 10-19.
- Al-Tahan, Y.H., Amien, S, Hasan, H.A. 1995. "The effect of plowing in field efficiency by moldboard plow and disk plow. *Journal of Rafidain* 27(1). pp. 77-8.
- Azawi, A., Turkey, T., Isaak, M. (2024). Sustainable Energy Use for Mechanized Wheat Production Systems in Iraq. *Tikrit Journal for Agricultural Sciences*, 24(2), 115 – 130
- Bukhari, S.B, M.A, Bhutto, J.M. Baloch, A.B. Bbhattu. and A.N. Mariani .1988" edition. AV1 Publishing Company. U.S.A.
- Firas J. Alsaady.2013. Studying the effect of tillage depths and practical speed of mechanical unit on some of soil physical properties and the growth of Mize. *Al-Furat Journal Agricultural sciences*.5 (3) pp. 287-280.
- Ghofran, S.A. 2022. The effect of practical speeds and adding weight on some performance indicators for New Holland tractor M.Sc. Theses. Agricultural College. University of Baghdad. pp.34-46.
- Ghali, A.A.2019. Effect of soil moisture and tillage depth on some mechanical for tillage machine type moldboard plow. *Journal of University of Babylon for pure and applied sciences* .27 (2). Pp. 195-207.
- Galib AA Alkaab. 2024 Synthesis a mechanical harvester to increase performance efficiency and reduce losses. *International Journal of Research in Agronomy* 2024; 7(2): 309-312. DOI: <https://doi.org/10.33545/2618060X.2024.v7.i2e.320>.
- Galib AA Alkaab., and W. AH Al-Sheikh. 2024. The cylinder speeds and clearance sieves on evaluating the performance of the New Holland combine harvester. *South Asian Journal of Agricultural Sciences* 2024; 4(1): 01-03.
- Isaak, M. and Ahmed, M.A. (2009). Effect of two plow types and different plowing speed on some soil physical properties and some field technical indications. *Tikrit University Journal of Agricultural Sciences*, 9(1): 357–366.
- Isaak, M. (2011). Effect of some tilt angles of disc plow and tillage speeds on some soil physical and vitality properties in gypseous soil. *Journal Of Kirkuk University for Agricultural Sciences*, 2(1): 115–123.

- Jyoti¹, B. K.V.S. Ram Reddy., Chetankumar P. Sawant¹, A.P. Pandirwar¹, R.R. Potdar¹ and R.D. Randhe. (2019). Predicting Draft Requirement of Tillage Implements Using Pull Type Load Cell in Southern Region of Andhra Pradesh, India. *Int.J. Curr. Microbiol. App. Sci* (2019) 8(1): 606-612.
- Kareem, I. Kareem, P. Sven. Polytechnic Journal. 2019. Effect of Plough Depth, Tractor Forward Speed, and Plough Types on the Fuel Consumption and Performance. *Polytechnic Journal*. 9(1) pp.43-49.
- Kim, Y.S., W.S. Kim, S.M. Beak., Y.J. Kim (2020) Analysis of Tillage Depth and Gear Selection for Mechanical Load and Fuel Efficiency of an Agricultural Tractor Using an Agricultural Field Measuring System. DOI.3390/s20092450. Article in Sensors. April 2020. <https://www.ResearchGate.net/publication/340994066>.
- K. Z. Amer. 2017. Effect of different speed of two plows on some machinery unit performance indicators. *Iraqi Journal of Agricultural Sciences* –0010-0014: (1) pp. 48.
- Kepner R.A; R. and Bainer, E.L. Barger 1982. Principles of farm machinery. 3rd Performance of selected tillage implements. *J.AMA*.19(14). pp. 9-14 .
- Laith A.Z. AL-Hashimy. 2012. The effect of disc tilt angle, tillage speed and depth on some of machinery unit technical and energy requirements. *Iraqi Journal Agricultural Science* 33 (1). pp. 131-143.
- Mankhi, M.A., 2012. Evaluation the performance of machinery unit Massey Ferguson tractor MF-650 and calculate the economic costs under different speeds, depths and tires pressure. M.Sc. thesis. Agricultural College University of Baghdad pp. 44-49.
- M, Isaak., A, Azawi and TH, Turkey .2024. Influence of various tillage systems and tillage speed on some soil physical properties. *Progress in Agricultural Engineering Sciences*. Dio10.1556/446.
- Silas, O. N, & Raymond, A.E. 2020. Evaluation of the Effects of Tract Forward Speed and Tillage Depth on Fuel Consumption during Plowing Operation. *Journal of New views in Engineering and Technology*. Vol 2, Issue 2, June, 2020.
- Th, Abdul-Kreem. 2017. Study of some mechanical indicators for different mechanized units of tillage system under Gypseous soil condition. *Tikrit University Journal of Agricultural*. 17 (2). 203 – 213.